



Business Sector Market Assessment and Baseline Study: Industrial: Appendices

Vol. 2

Final Report



Prepared for the Vermont Department of Public Service

Madison, Wisconsin, September 25, 2009



Table of Contents

- List of Exhibits:iii
- Appendix A: General** A-1
 - A.1. Premise Weighted Results A-1
- Appendix B: Indoor Lighting** B-5
 - B.1. Types of Indoor Lighting B-5
 - B.1.1. Facility kWh Weighted Results B-5
 - B.1.2. Premise Weighted Results B-6
 - B.2. Lighting Densities B-7
 - B.3. Usage B-12
 - B.3.1. Facility kWh Weighted Results B-12
 - B.3.2. Premise Weighted Results B-18
 - B.4. Ballast Types B-24
 - B.4.1. Facility kWh Weighted Results B-24
 - B.4.2. Premise Weighted Results B-28
 - B.5. Control Types B-33
 - B.5.1. Facility kWh Weighted Results B-33
 - B.5.2. Premise Weighted Results B-34
 - B.6. Energy Efficient Opportunities B-35
 - B.6.1. Facility kWh Weighted Results B-35
 - B.6.2. Premise Weighted Results B-48
- Appendix C: Motors** C-61
 - C.1. Premise Weighted Results C-61
 - C.1.1. Motor Details C-61
 - C.1.2. Motor Energy Efficiency Opportunities C-81
- Appendix D: Compressed Air Systems** D-82
 - D.1. Facility kWh Weighted Results D-82
 - D.1.1. Compressed Air Details D-82
 - D.2. Premise Weighted Results D-86
 - D.2.1. Compressed Air Details D-86
- Appendix E: Refrigeration Results** E-86
- Appendix F: Cooling Results** F-87
 - F.1. Premise Weighted Results F-87
 - F.1.1. Overall Cooling F-87



Table of Contents

- F.1.2. Central Cooling Plant.....F-90
- F.2. Packaged CoolingF-95
 - F.2.1. Premise Weighted ResultsF-95
- Appendix G: Heating Results G-99**
 - G.1. Premise Weighted Results G-99
 - G.1.1. Central Heating Plant..... G-99
 - G.2. Miscellaneous Heating G-105
 - G.2.1. Premise Weighted Results G-105



Table of Contents

List of Exhibits:

Table A-1 Building Type by Geo-Target (Premise)	A-1
Table A-2 Systems Upgraded in Past 5 Years by Geo-Target (Premise).....	A-1
Table A-3 Square Footage of Conditioned Floor Space by Geo-Target (Premise)	A-2
Table A-4 Average Floorspace by Geo-Target (Premise)	A-2
Table A-5 Ownership Status by Geo-Target (Premise)	A-3
Table A-6 Secondary Economic Use by Geo-Target (Premise)	A-3
Table A-7 Year Built by Geo-Target (Premise)	A-4
Table B-1 Types of Indoor Lighting (Facility kWh)	B-5
Table B-2 Types of Indoor Lighting (Premise)	B-6
Table B-3 Default Values Used For Missing Data	B-7
Table B-4 Overall Light Density	B-8
Table B-5 Incan Density.....	B-8
Table B-6 CFL Light Density	B-8
Table B-7 HID Light Density	B-9
Table B-8 T5 Light Density	B-9
Table B-9 Std T8 Light Density	B-9
Table B-10 HP T8 Light Density	B-10
Table B-11 Unk T8 Light Density	B-10
Table B-12 T12 Light Density	B-10
Table B-13 Unk FL Tube Light Density.....	B-11
Table B-14 Other Fluor Light Density	B-11
Table B-15 Other Light Density.....	B-11
Table B-16 Quartz Light Density.....	B-12
Table B-17 Overall Light Usage (Facility kWh)	B-12
Table B-18 HID Light Usage (Facility kWh)	B-13
Table B-19 T5 Light Usage (Facility kWh)	B-13
Table B-20 Standard T8 Light Usage (Facility kWh).....	B-14
Table B-21 High Performance T8 Light Usage (Facility kWh)	B-14
Table B-22 Unknown T8 Light Usage (Facility kWh)	B-15
Table B-23 T12 Light Usage (Facility kWh)	B-15
Table B-24 Unknown Fluorescent Tube Light Usage (Facility kWh)	B-16
Table B-25 Other Fluorescent Light Usage (Facility kWh).....	B-16



Table of Contents

Table B-26 Other Light Usage (Facility kWh)	B-17
Table B-27 Quartz Light Usage (Facility kWh).....	B-17
Table B-28 Overall Light Usage (Premise)	B-18
Table B-29 HID Light Usage (Premise)	B-18
Table B-30 T5 Light Usage (Premise)	B-19
Table B-31 Standard T8 Light Usage (Premise).....	B-19
Table B-32 High Performance T8 Light Usage (Premise)	B-20
Table B-33 Unknown T8 Light Usage (Premise)	B-20
Table B-34 T12 Light Usage (Premise)	B-21
Table B-35 Unknown Fluorescent Tube Light Usage (Premise).....	B-21
Table B-36 Other Fluorescent Light Usage (Premise).....	B-22
Table B-37 Other Light Usage (Premise).....	B-22
Table B-38 Quartz Light Usage (Premise).....	B-23
Table B-39 Overall Light Ballast Types (Facility kWh).....	B-24
Table B-40 HID Light Ballast Types (Facility kWh)	B-25
Table B-41 T5 Light Ballast Types (Facility kWh)	B-25
Table B-42 Standard T8 Light Ballast Types (Facility kWh)	B-26
Table B-43 High Performance T8 Light Ballast Types (Facility kWh)	B-26
Table B-44 Unknown T8 Light Ballast Types (Facility kWh)	B-27
Table B-45 T12 Light Ballast Types (Facility kWh)	B-27
Table B-46 Other Fluorescent Light Ballast Types (Facility kWh)	B-28
Table B-47 Overall Light Ballast Types (Premise).....	B-28
Table B-48 HID Light Ballast Types (Premise)	B-29
Table B-49 T5 Light Ballast Types (Premise)	B-29
Table B-50 Standard T8 Light Ballast Types (Premise).....	B-30
Table B-51 High Performance T8 Light Ballast Types (Premise)	B-30
Table B-52 Unknown T8 Light Ballast Types (Premise)	B-31
Table B-53 T12 Light Ballast Types (Premise)	B-31
Table B-54 Other Fluorescent Light Ballast Types (Premise).....	B-32
Table B-55 Overall Light Control Types (Facility kWh)	B-33
Table B-56 Overall Light Control Types (Premise)	B-34
Table B-57 Overall EE Opportunities (Facility kWh)	B-35
Table B-58 Incandescent EE Opportunities (Facility kWh)	B-36



Table of Contents

Table B-59 CFL EE Opportunities (Facility kWh).....	B-37
Table B-60 HID EE Opportunities (Facility kWh)	B-38
Table B-61 T5 EE Opportunities (Facility kWh)	B-39
Table B-62 St T8 EE Opportunities (Facility kWh).....	B-40
Table B-63 High Performance T8 EE Opportunities (Facility kWh)	B-41
Table B-64 Unknown T8 EE Opportunities (Facility kWh)	B-42
Table B-65 T12 EE Opportunities (Facility kWh)	B-43
Table B-66 Unknown Fluorescent Tube EE Opportunities (Facility kWh)	B-44
Table B-67 Other Fluorescent EE Opportunities (Facility kWh).....	B-45
Table B-68 Other Light Type EE Opportunities (Facility kWh).....	B-46
Table B-69 Quartz EE Opportunities (Facility kWh).....	B-47
Table B-70 Overall EE Opportunities (Premise)	B-48
Table B-71 Incandescent EE Opportunities (Premise)	B-49
Table B-72 CFL EE Opportunities (Premise).....	B-50
Table B-73 HID EE Opportunities (Premise)	B-51
Table B-74 T5 EE Opportunities (Premise)	B-52
Table B-75 St T8 EE Opportunities (Premise)	B-53
Table B-76 High Performance T8 EE Opportunities (Premise)	B-54
Table B-77 Unknown T8 EE Opportunities (Premise)	B-55
Table B-78 T12 EE Opportunities (Premise)	B-56
Table B-79 Unknown Fluorescent Tube EE Opportunities (Premise).....	B-57
Table B-80 Other Fluorescent EE Opportunities (Premise).....	B-58
Table B-81 Other Light Type EE Opportunities (Premise).....	B-59
Table B-82 Quartz EE Opportunities (Premise).....	B-60
Table C-1 Motors by Size Category	C-61
Table C-2 Motor Horespower by Size Category	C-62
Table C-3 NEMA Motor HP as a Percent of Total Motor HP by Size Category	C-63
Table C-4 NEMA Motor HP as a Percent of Size Category HP	C-64
Table C-5 NEMA Motor HP by Size Category	C-65
Table C-6 Variable Load HP as a Percent of Total HP	C-66
Table C-7 Variable Load HP as a Percent of Size Category HP	C-67
Table C-8 Variable Load HP by Size Category.....	C-68
Table C-9 VFD Motor HP as a Percent of Total HP.....	C-69



Table of Contents

Table C-10 VFD Motor HP as a Percent of Size Category HP	C-70
Table C-11 VFD Motor HP by Size Category	C-71
Table C-12 Percent of Size Category Variable Load HP with VFDs.....	C-72
Table C-13 Average Number of Motors per Facility (Premise)	C-73
Table C-14 Average Total Horsepower of Motors per Facility (Premise).....	C-74
Table C-15 Average Total Horsepower of NEMA Premium Motors per Facility (Premise).....	C-75
Table C-16 Average Total Horsepower of Motors with Variable Loads per Facility (Premise).....	C-76
Table C-17 Average Total Horsepower of Motors with VFDs per Facility (Premise)	C-77
Table C-18 Percent of Total Motor Horsepower by End-Use (Premise)	C-78
Table C-19 Percent of Motors Associated with Component Type (Premise).....	C-79
Table C-20 Percent of Motors with Load Modulation Type (Premise)	C-80
Table C-21 Percent of Motors by Type (Premise)	C-80
Table C-22 Percent of Motors with Enclosure Type (Premise).....	C-81
Table C-23 Miscellaneous Motor Details (Premise).....	C-81
Table C-24 Motor EE Ops (Premise)	C-81
Table D-1 Percent of Facilities with Air Compressor End Uses (Facility kWh)	D-82
Table D-2 Air Compressor Details (Facility kWh)	D-83
Table D-3 Air Dryer System Details (Facility kWh)	D-83
Table D-4 Percent of Facilities with Compressed Air Unit Type (Facility kWh).....	D-84
Table D-5 Percent of Facilities with Compressed Air Fuel Types (Facility kWh)	D-84
Table D-6 Percent of Facilities with Compressed Air Control Type (Facility kWh)	D-85
Table D-7 Compressed Air EE Opportunities (Facility kWh)	D-85
Table D-8 Percent of Facilities with Air Compressor End Uses (Premise)	D-86
Table D-9 Horsepower Devoted to Compressed Air per Facility (Premise).....	D-86
Table E-1 Commercial Refrigerator Details	E-86
Table E-2 Non-Commercial Refrigerator Details	E-86
Table F-1 Percent of Facilities with Space Cooling of Type (Premise).....	F-87
Table F-2 Percent of Units with Space Cooling of Type (Premise).....	F-88
Table F-3 Overall Space Cooling Details (Premise)	F-89
Table F-4 Percent of Facilities with Central Cooling Plants by Type (Premise).....	F-90
Table F-5 Percent of Central Cooling Plant Premises by Type (Premise).....	F-90
Table F-6 Percent of Central Cooling Plant Premises by Fuel (Premise).....	F-91
Table F-7 Percent of Central Cooling Plant Cooling Equipment Units by Fuel (Premise)	F-91



Table of Contents

Table F-8 Output (Tons) of Central Cooling Plant Equipment (Premise).....	F-92
Table F-9 EE Ops for Central Cooling Plant Fans and Blowers (Premise).....	F-92
Table F-10 EE Ops for Packaged Central Cooling Plants (Premise).....	F-93
Table F-11 Average Operating Weeks of Central Cooling Plants (Premise)	F-93
Table F-12 Average Operating Hours of Central Cooling Plants (Premise).....	F-94
Table F-13 Unit Type by Geo-Target (premise).....	F-95
Table F-14 Number of Units of a Common Size and Type by Geo-Target (premise).....	F-96
Table F-15 Rated Output by Geo-Target (premise).....	F-96
Table F-16 Heating Fuel by Geo-Target (premise).....	F-97
Table F-17 Equipment Share by Unit Type by Geo-Target (premise)	F-97
Table F-18 Average Values by Geo-Target (premise).....	F-98
Table G-1 Percent of Facilities with Central Heating Plant of Type (Premise).....	G-99
Table G-2 Percent of Units with Central Heating Plant of Type (Premise)	G-100
Table G-3 Central Heating Plant Output (Premise)	G-100
Table G-4 Central Heating Plant Output Categories (Premise)	G-101
Table G-5 Central Heating Plant Details (Premise)	G-102
Table G-6 Central Heating Plant Age Categories (Premise)	G-103
Table G-7 Central Heating Plant EE Ops	G-104
Table G-8 Number of Units of the Same Size and Type by Geo-Target (Premise)	G-105
Table G-9 Percent of Output Used for Space Heat by Geo-Target (Premise).....	G-106
Table G-10 Percent of Output Used for Process Heat by Geo-Target (Premise).....	G-106
Table G-11 Percent of Output for Other Uses by Geo-Target (Premise).....	G-107
Table G-12 Average Values by Geo-Target (Premise).....	G-107
Table G-13 Heating Equipment Type by Geo-Target (Premise).....	G-108
Table G-14 Heating Fuel by Geo-Target (Premise).....	G-108
Table G-15 Energy Star Equipment by Geo-Target (Premise)	G-109
Table G-16 Quantity of Fans by Geo-Target (Premise).....	G-109
Table G-17 Rated Output in Mbtuh by Geo-Target (Premise).....	G-110



Appendix A: General

A.1. Premise Weighted Results

**Table A-1
Building Type by Geo-Target (Premise)**

Building Type	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Multiple building complex	All Industrial	24	36%	14%	57%
	Geo	5	79%	54%	105%
	Non-Geo	19	25%	4%	47%
Single stand-alone building	All Industrial	24	64%	43%	86%
	Geo	5	21%	-5%	46%
	Non-Geo	19	75%	53%	96%

**Table A-2
Systems Upgraded in Past 5 Years by Geo-Target (Premise)**

System Type	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Heating and ventilation	All Industrial	23	15%	-3%	33%
	Geo	5	0%	0%	0%
	Non-Geo	18	19%	-3%	41%
AC	All Industrial	23	1%	-1%	3%
	Geo	5	0%	0%	0%
	Non-Geo	18	2%	-1%	4%
Lighting	All Industrial	23	30%	12%	49%
	Geo	5	21%	-5%	46%
	Non-Geo	18	33%	10%	55%
Refrigeration	All Industrial	23	15%	-3%	33%
	Geo	5	0%	0%	0%
	Non-Geo	18	19%	-3%	41%
None of the above	All Industrial	23	38%	16%	59%
	Geo	5	79%	54%	105%
	Non-Geo	18	28%	6%	50%



**Table A-3
Square Footage of Conditioned Floor Space by Geo-Target (Premise)**

Square Footage	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
2,000 and Under	All Industrial	38	2%	-1%	4%
	Geo	13	0%	0%	0%
	Non-Geo	25	2%	-1%	5%
2,001-5,000	All Industrial	38	19%	-1%	38%
	Geo	13	0%	0%	0%
	Non-Geo	25	24%	0%	49%
5,001-10,000	All Industrial	38	5%	1%	9%
	Geo	13	0%	0%	0%
	Non-Geo	25	6%	1%	12%
10,001-20,000	All Industrial	38	60%	39%	80%
	Geo	13	75%	50%	101%
	Non-Geo	25	55%	30%	80%
20,001-50,000	All Industrial	38	6%	2%	10%
	Geo	13	14%	-3%	30%
	Non-Geo	25	3%	0%	7%
Over 50,000	All Industrial	38	9%	4%	15%
	Geo	13	11%	-2%	24%
	Non-Geo	25	9%	3%	15%

**Table A-4
Average Floorspace by Geo-Target (Premise)**

Area	Average FloorSpace	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
All Industrial	23,760	38	16,669	30,186,526
Geo	24,591	13	14,397	4,808,517
Non-Geo	23,509	25	14,595	20,855,807



**Table A-5
Ownership Status by Geo-Target (Premise)**

Ownership Status	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Own and occupy the entire facility	All Industrial	44	55%	34%	76%
	Geo	14	25%	-1%	50%
	Non-Geo	30	62%	38%	85%
Own the entire facility and occupy a part of it	All Industrial	44	13%	-2%	29%
	Geo	14	68%	37%	99%
	Non-Geo	30	0%	0%	0%
Lease the entire facility from another organization	All Industrial	44	17%	0%	33%
	Geo	14	19%	-1%	39%
	Non-Geo	30	7%	-4%	17%
Lease a portion of the facility from another organization	All Industrial	44	14%	-2%	31%
	Geo	14	18%	-3%	38%
	Non-Geo	30	17%	0%	33%
Other ownership arrangement	All Industrial	44	1%	0%	3%
	Geo	14	2%	-1%	4%
	Non-Geo	30	1%	0%	2%

**Table A-6
Secondary Economic Use by Geo-Target (Premise)**

Secondary Economic Use?	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
No	All Industrial	29	82%	65%	100%
	Geo	7	99%	97%	101%
	Non-Geo	22	78%	57%	99%
Yes	All Industrial	29	18%	0%	35%
	Geo	7	0%	0%	0%
	Non-Geo	22	22%	1%	43%



**Table A-7
Year Built by Geo-Target (Premise)**

Year Built	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Unknown	All Industrial	44	31%	10%	51%
	Geo	14	1%	0%	3%
	Non-Geo	30	38%	14%	62%
Before 1900	All Industrial	44	2%	0%	4%
	Geo	14	0%	0%	0%
	Non-Geo	30	2%	0%	5%
1900-1959	All Industrial	44	3%	0%	5%
	Geo	14	0%	0%	0%
	Non-Geo	30	3%	0%	6%
1960-1969	All Industrial	44	2%	0%	4%
	Geo	14	2%	0%	4%
	Non-Geo	30	2%	-1%	4%
1970-1979	All Industrial	44	19%	3%	34%
	Geo	14	76%	51%	100%
	Non-Geo	30	5%	1%	9%
1980-1989	All Industrial	44	7%	3%	12%
	Geo	14	14%	-3%	30%
	Non-Geo	30	6%	1%	10%
1990-2000	All Industrial	44	36%	15%	56%
	Geo	14	7%	-3%	18%
	Non-Geo	30	43%	19%	66%
After 2000	All Industrial	44	2%	0%	4%
	Geo	14	0%	0%	0%
	Non-Geo	30	2%	0%	5%



Appendix B: Indoor Lighting

B.1. Types of Indoor Lighting

B.1.1. Facility kWh Weighted Results

**Table B-1
Types of Indoor Lighting (Facility kWh)**

Light Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Incandescent	All Industrial	10%	43	4%	15%
	Geo	9%	13	0%	19%
	Non-Geo	10%	30	3%	17%
CFL	All Industrial	10%	43	4%	16%
	Geo	17%	13	-3%	36%
	Non-Geo	8%	30	3%	13%
HID	All Industrial	25%	43	18%	33%
	Geo	21%	13	7%	36%
	Non-Geo	27%	30	19%	35%
T5	All Industrial	7%	43	3%	12%
	Geo	7%	13	0%	14%
	Non-Geo	8%	30	3%	13%
Standard T8	All Industrial	41%	43	28%	53%
	Geo	43%	13	26%	60%
	Non-Geo	40%	30	25%	55%
High Performance T8	All Industrial	6%	43	2%	10%
	Geo	11%	13	1%	21%
	Non-Geo	4%	30	0%	8%
T12	All Industrial	36%	43	27%	46%
	Geo	41%	13	23%	59%
	Non-Geo	35%	30	23%	46%
Quartz	All Industrial	2%	43	0%	4%
	Geo	7%	13	-2%	15%
	Non-Geo	1%	30	0%	1%
Other Fluorescent	All Industrial	5%	43	2%	8%
	Geo	9%	13	2%	16%
	Non-Geo	4%	30	0%	8%
Unknown Fluorescent Tube	All Industrial	3%	43	1%	6%
	Geo	8%	13	-1%	18%
	Non-Geo	2%	30	0%	3%
Other	All Industrial	7%	43	3%	11%
	Geo	9%	13	2%	17%
	Non-Geo	7%	30	2%	11%
Unknown T8	All Industrial	15%	43	8%	23%
	Geo	19%	13	0%	39%
	Non-Geo	14%	30	6%	23%



B.1.2. Premise Weighted Results

**Table B-2
Types of Indoor Lighting (Premise)**

Light Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Incandescent	All Industrial	15%	43	0%	31%
	Geo	69%	13	39%	100%
	Non-Geo	3%	30	0%	5%
CFL	All Industrial	18%	43	1%	35%
	Geo	1%	13	0%	2%
	Non-Geo	22%	30	2%	42%
HID	All Industrial	39%	43	19%	60%
	Geo	3%	13	0%	5%
	Non-Geo	48%	30	24%	71%
T5	All Industrial	20%	43	3%	37%
	Geo	7%	13	-3%	18%
	Non-Geo	23%	30	3%	43%
Standard T8	All Industrial	64%	43	43%	84%
	Geo	97%	13	93%	100%
	Non-Geo	56%	30	32%	79%
High Performance T8	All Industrial	3%	43	0%	6%
	Geo	7%	13	-3%	18%
	Non-Geo	2%	30	0%	5%
T12	All Industrial	57%	43	36%	77%
	Geo	16%	13	-2%	35%
	Non-Geo	66%	30	46%	87%
Quartz	All Industrial	4%	43	1%	7%
	Geo	7%	13	-4%	17%
	Non-Geo	3%	30	0%	6%
Other Fluorescent	All Industrial	18%	43	1%	35%
	Geo	13%	13	-3%	29%
	Non-Geo	19%	30	-1%	39%
Unknown Fluorescent Tube	All Industrial	16%	43	0%	32%
	Geo	69%	13	38%	99%
	Non-Geo	4%	30	0%	7%
Other	All Industrial	9%	43	4%	14%
	Geo	20%	13	-2%	42%
	Non-Geo	6%	30	2%	11%
Unknown T8	All Industrial	17%	43	0%	34%
	Geo	2%	13	0%	4%
	Non-Geo	20%	30	0%	40%



B.2. Lighting Densities

Table B-3
Default Values Used For Missing Data

HID		
	Magnetic	Electronic
Lamp Quantity per ballast	1	1
MH or HPS <=100W	90	NA
250W MH HID	295	270
320W MH HID	365	345
350W MH HID	400	375
400W MH HID	458	430
250W HPS HID	295	NA
310W HPS HID	365	NA
400W HPS HID	465	NA

Source: Efficiency Vermont Technical Reference User Manual No. 2008-53
Source: Advance Atlas 2008-2009, based on 277V systems

CFL												
Lamp Quantity per ballast	Magnetic				Magnetic Energy Saving				Electronic			
	1	2	3	4	1	2	3	4	1	2	3	4
CFL <20W	15	35	NA	NA	NA	NA	NA	NA	14	27	NA	NA
CFL >=20W	29	50	NA	NA	NA	NA	NA	NA	27	51	NA	NA
Dimming CFL <20W	20	NA	NA	NA	NA	NA	NA	NA	18	33	86	112
Dimming CFL >=20W	25	NA	NA	NA	NA	NA	NA	NA	31	58	NA	NA

Source: Efficiency Vermont Technical Reference User Manual No. 2008-53
Source: Advance Atlas 2008-2009, based on 277V systems
Source: Advance Atlas 2008-2009, based on 277V systems (assumed 13W lamps for <20W and 26W lamps for >=20W)

Fluorescent												
Lamp Quantity per ballast	Magnetic				Magnetic Energy Saving				Electronic			
	1	2	3	4	1	2	3	4	1	2	3	4
T5	NA	NA	NA	NA	NA	NA	NA	NA	32	64	96	128
T5HO	NA	NA	NA	NA	NA	NA	NA	NA	62	117	179	234
T8	41	76	NA	NA	NA	NA	NA	NA	29	55	86	112
HPT8	NA	NA	NA	NA	NA	NA	NA	NA	28	59	87	108
T10	53	88	NA	NA	NA	NA	NA	NA	35	71	112	NA
T12	50	86	NA	172	43	72	103	144	35	71	107	NA

Source: Efficiency Vermont Technical Reference User Manual No. 2008-53
Source: Advance Atlas 2008-2009, based on 277V systems
Average wattage based on CEE Approved ballasts

Operating Hours	
Building Type	Annual Hours
Office	3435
Restaurant	4156
Retail	3068
Grocery/Supermarket	4612
Warehouse	2388
Elem/Sec School	2080
College	5010
Health	3392
Hospital	4532
Hotel/Motel	2697
Manufacturing	3500
Other/misc.	2278

Source: Efficiency Vermont Technical



**Table B-4
Overall Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.76	43	0.64	0.88
	Geo	0.84	13	0.77	0.91
	Non-Geo	0.74	30	0.59	0.89
Total Lighting kWh per Premise	All Industrial	64,554,620	43	47,223,374	81,885,865
	Geo	90,725,980	13	58,706,022	122,745,938
	Non-Geo	58,360,278	30	39,374,258	77,346,299
Watts per Fixture	All Industrial	122.14	35	99.30	144.97
	Geo	96.02	11	73.39	118.65
	Non-Geo	137.67	24	110.46	164.88

**Table B-5
Incan Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.25	1	0.25	0.25
	Geo	0.25	1	0.25	0.25
	Non-Geo	.	0	.	.
Total Lighting kWh per Premise	All Industrial	858,000	1	858,000	858,000
	Geo	858,000	1	858,000	858,000
	Non-Geo	.	0	.	.
Watts per Fixture	All Industrial	75.00	1	75.00	75.00
	Geo	75.00	1	75.00	75.00
	Non-Geo	.	0	.	.

**Table B-6
CFL Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.09	2	0.04	0.13
	Geo	.	0	.	.
	Non-Geo	0.09	2	0.04	0.13
Total Lighting kWh per Premise	All Industrial	629,461	2	546,984	711,938
	Geo	.	0	.	.
	Non-Geo	629,461	2	546,984	711,938
Watts per Fixture	All Industrial	24.56	2	24.33	24.79
	Geo	.	0	.	.
	Non-Geo	24.56	2	24.33	24.79



**Table B-7
HID Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.45	9	0.36	0.53
	Geo	0.47	3	0.28	0.66
	Non-Geo	0.44	6	0.34	0.53
Total Lighting kWh per Premise	All Industrial	19,175,707	9	10,193,383	28,158,032
	Geo	310,130,010	3	215,842,321	404,417,700
	Non-Geo	13,792,166	6	9,942,063	17,642,269
Watts per Fixture	All Industrial	368.39	9	324.30	412.47
	Geo	446.30	3	426.91	465.70
	Non-Geo	339.75	6	293.88	385.62

**Table B-8
T5 Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.27	6	0.11	0.43
	Geo	0.40	1	0.40	0.40
	Non-Geo	0.26	5	0.09	0.43
Total Lighting kWh per Premise	All Industrial	25,592,535	6	4,393,016	46,792,054
	Geo	54,247,864	1	54,247,864	54,247,864
	Non-Geo	23,641,105	5	2,617,724	44,664,486
Watts per Fixture	All Industrial	241.03	6	172.26	309.80
	Geo	252.72	1	252.72	252.72
	Non-Geo	239.93	5	164.75	315.10

**Table B-9
Std T8 Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.56	24	0.43	0.70
	Geo	0.62	8	0.47	0.78
	Non-Geo	0.51	16	0.32	0.71
Total Lighting kWh per Premise	All Industrial	25,531,545	24	15,927,882	35,135,208
	Geo	45,646,049	8	35,183,094	56,109,004
	Non-Geo	17,040,804	16	8,654,187	25,427,421
Watts per Fixture	All Industrial	70.47	24	64.41	76.54
	Geo	77.72	8	65.63	89.81
	Non-Geo	64.05	16	58.49	69.62



**Table B-10
HP T8 Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.49	4	0.21	0.78
	Geo	0.24	2	0.16	0.31
	Non-Geo	0.88	2	0.83	0.93
Total Lighting kWh per Premise	All Industrial	73,979,140	4	(994,671)	148,952,950
	Geo	39,227,183	2	12,177,578	66,276,788
	Non-Geo	101,699,032	2	(33,680,194)	237,078,259
Watts per Fixture	All Industrial	112.06	4	94.63	129.49
	Geo	109.28	2	98.23	120.33
	Non-Geo	113.21	2	89.54	136.88

**Table B-11
Unk T8 Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.52	2	0.36	0.67
	Geo	0.28	1	0.28	0.28
	Non-Geo	0.65	1	0.65	0.65
Total Lighting kWh per Premise	All Industrial	73,447,545	2	47,946,630	98,948,460
	Geo	232,895,520	1	232,895,520	232,895,520
	Non-Geo	58,464,806	1	58,464,806	58,464,806
Watts per Fixture	All Industrial	131.90	2	130.59	133.20
	Geo	135.72	1	135.72	135.72
	Non-Geo	131.04	1	131.04	131.04

**Table B-12
T12 Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.30	17	0.16	0.44
	Geo	0.24	5	0.18	0.29
	Non-Geo	0.31	12	0.14	0.48
Total Lighting kWh per Premise	All Industrial	13,515,073	17	4,259,067	22,771,078
	Geo	33,003,691	5	30,367,636	35,639,747
	Non-Geo	12,425,074	12	3,083,987	21,766,162
Watts per Fixture	All Industrial	118.12	17	83.52	152.72
	Geo	103.85	5	86.24	121.46
	Non-Geo	120.66	12	79.84	161.48



**Table B-13
Unk FL Tube Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	2.13	2	2.05	2.20
	Geo	2.17	1	2.17	2.17
	Non-Geo	1.72	1	1.72	1.72
Total Lighting kWh per Premise	All Industrial	14,260,947	2	13,191,492	15,330,402
	Geo	14,892,134	1	14,892,134	14,892,134
	Non-Geo	7,879,872	1	7,879,872	7,879,872
Watts per Fixture	All Industrial	89.38	2	87.63	91.12
	Geo	90.40	1	90.40	90.40
	Non-Geo	78.72	1	78.72	78.72

**Table B-14
Other Fluor Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.91	4	(0.04)	1.86
	Geo	0.06	2	0.04	0.09
	Non-Geo	1.28	2	(0.02)	2.59
Total Lighting kWh per Premise	All Industrial	20,654,595	3	16,154,247	25,154,943
	Geo	1,537,536	1	1,537,536	1,537,536
	Non-Geo	22,211,673	2	19,248,435	25,174,912
Watts per Fixture	All Industrial	636.81	4	217.35	1,056.27
	Geo	52.95	2	49.84	56.05
	Non-Geo	842.27	2	428.12	1,256.41

**Table B-15
Other Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.00	5	0.00	0.00
	Geo	0.00	3	0.00	0.01
	Non-Geo	0.00	2	0.00	0.00
Total Lighting kWh per Premise	All Industrial	485,602	5	337,173	634,031
	Geo	472,105	3	343,234	600,977
	Non-Geo	499,320	2	230,193	768,447
Watts per Fixture	All Industrial	5.70	5	5.30	6.09
	Geo	6.00	3	6.00	6.00
	Non-Geo	5.43	2	4.67	6.19



**Table B-16
Quartz Light Density**

Statistic	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Lighting Power Density (W/sqft)	All Industrial	0.48	2	0.28	0.68
	Geo	.	0	.	.
	Non-Geo	0.48	2	0.28	0.68
Total Lighting kWh per Premise	All Industrial	2,548,975	2	235,849	4,862,101
	Geo	.	0	.	.
	Non-Geo	2,548,975	2	235,849	4,862,101
Watts per Fixture	All Industrial	95.37	2	88.35	102.39
	Geo	.	0	.	.
	Non-Geo	95.37	2	88.35	102.39

B.3. Usage

B.3.1. Facility kWh Weighted Results

**Table B-17
Overall Light Usage (Facility kWh)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	96%	35	94%	98%
	Geo	97%	11	94%	99%
	Non-Geo	96%	24	93%	99%
Task	All Industrial	1%	35	0%	1%
	Geo	1%	11	0%	2%
	Non-Geo	0%	24	0%	1%
Exit	All Industrial	1%	35	0%	1%
	Geo	1%	11	0%	2%
	Non-Geo	0%	24	0%	1%
Display	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
Other	All Industrial	0%	35	0%	1%
	Geo	0%	11	0%	0%
	Non-Geo	1%	24	0%	1%
Unknown	All Industrial	2%	35	0%	4%
	Geo	1%	11	-1%	3%
	Non-Geo	3%	24	0%	6%



**Table B-18
HID Light Usage (Facility kWh)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	95%	13	90%	100%
	Geo	100%	3	100%	100%
	Non-Geo	91%	10	84%	99%
Task	All Industrial	0%	13	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	10	0%	0%
Exit	All Industrial	0%	13	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	10	0%	0%
Display	All Industrial	0%	13	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	10	0%	0%
Other	All Industrial	3%	13	-1%	6%
	Geo	0%	3	0%	0%
	Non-Geo	4%	10	-2%	11%
Unknown	All Industrial	2%	13	-1%	6%
	Geo	0%	3	0%	0%
	Non-Geo	4%	10	-1%	9%

**Table B-19
T5 Light Usage (Facility kWh)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	100%	6	100%	100%
	Geo	100%	1	100%	100%
	Non-Geo	100%	5	100%	100%
Task	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Exit	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Display	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Other	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Unknown	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%



**Table B-20
Standard T8 Light Usage (Facility kWh)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	96%	25	92%	100%
	Geo	99%	8	98%	100%
	Non-Geo	94%	17	87%	101%
Task	All Industrial	1%	25	0%	1%
	Geo	1%	8	0%	2%
	Non-Geo	1%	17	0%	1%
Exit	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	0%
Display	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	0%
Other	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	0%
Unknown	All Industrial	3%	25	-1%	8%
	Geo	0%	8	0%	0%
	Non-Geo	5%	17	-2%	12%

**Table B-21
High Performance T8 Light Usage (Facility kWh)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	100%	4	100%	100%
	Geo	100%	2	100%	100%
	Non-Geo	100%	2	100%	100%
Task	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Exit	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Display	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Unknown	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%



**Table B-22
Unknown T8 Light Usage (Facility kWh)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	88%	3	70%	105%
	Geo	80%	2	51%	110%
	Non-Geo	100%	1	100%	100%
Task	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Exit	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Display	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Other	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Unknown	All Industrial	12%	3	-5%	30%
	Geo	20%	2	-10%	49%
	Non-Geo	0%	1	0%	0%

**Table B-23
T12 Light Usage (Facility kWh)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	98%	18	97%	100%
	Geo	98%	5	96%	100%
	Non-Geo	98%	13	96%	101%
Task	All Industrial	1%	18	0%	1%
	Geo	2%	5	0%	4%
	Non-Geo	0%	13	0%	0%
Exit	All Industrial	0%	18	0%	0%
	Geo	0%	5	0%	0%
	Non-Geo	0%	13	0%	0%
Display	All Industrial	0%	18	0%	0%
	Geo	0%	5	0%	0%
	Non-Geo	0%	13	0%	0%
Other	All Industrial	0%	18	0%	0%
	Geo	0%	5	0%	0%
	Non-Geo	0%	13	0%	0%
Unknown	All Industrial	1%	18	0%	3%
	Geo	0%	5	0%	0%
	Non-Geo	2%	13	-1%	4%



**Table B-24
Unknown Fluorescent Tube Light Usage (Facility kWh)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	100%	4	100%	100%
	Geo	100%	1	100%	100%
	Non-Geo	100%	3	100%	100%
Task	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Exit	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Display	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Unknown	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%

**Table B-25
Other Fluorescent Light Usage (Facility kWh)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	80%	4	55%	104%
	Geo	100%	2	100%	100%
	Non-Geo	55%	2	9%	101%
Task	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Exit	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Display	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Other	All Industrial	20%	4	-4%	45%
	Geo	0%	2	0%	0%
	Non-Geo	45%	2	-1%	91%
Unknown	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%



**Table B-26
Other Light Usage (Facility kWh)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	79%	7	54%	103%
	Geo	0%	4	0%	0%
	Non-Geo	91%	3	76%	105%
Task	All Industrial	0%	7	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	3	0%	0%
Exit	All Industrial	21%	7	-3%	46%
	Geo	100%	4	100%	100%
	Non-Geo	9%	3	-5%	24%
Display	All Industrial	0%	7	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	3	0%	0%
Other	All Industrial	0%	7	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	3	0%	0%
Unknown	All Industrial	0%	7	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	3	0%	0%

**Table B-27
Quartz Light Usage (Facility kWh)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	78%	3	50%	107%
	Geo	100%	1	100%	100%
	Non-Geo	0%	2	0%	0%
Task	All Industrial	22%	3	-7%	50%
	Geo	0%	1	0%	0%
	Non-Geo	100%	2	100%	100%
Exit	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Display	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Other	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Unknown	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%



B.3.2. Premise Weighted Results

**Table B-28
Overall Light Usage (Premise)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	97%	35	95%	98%
	Geo	99%	11	97%	100%
	Non-Geo	96%	24	94%	98%
Task	All Industrial	1%	35	0%	1%
	Geo	0%	11	0%	0%
	Non-Geo	1%	24	0%	2%
Exit	All Industrial	1%	35	0%	1%
	Geo	1%	11	0%	2%
	Non-Geo	0%	24	0%	1%
Display	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
Other	All Industrial	1%	35	0%	2%
	Geo	0%	11	0%	0%
	Non-Geo	1%	24	0%	2%
Unknown	All Industrial	1%	35	0%	2%
	Geo	0%	11	0%	1%
	Non-Geo	1%	24	0%	3%

**Table B-29
HID Light Usage (Premise)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	94%	13	89%	100%
	Geo	100%	3	100%	100%
	Non-Geo	94%	10	87%	100%
Task	All Industrial	0%	13	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	10	0%	0%
Exit	All Industrial	0%	13	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	10	0%	0%
Display	All Industrial	0%	13	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	10	0%	0%
Other	All Industrial	4%	13	-1%	9%
	Geo	0%	3	0%	0%
	Non-Geo	5%	10	-1%	11%
Unknown	All Industrial	1%	13	0%	3%
	Geo	0%	3	0%	0%
	Non-Geo	2%	10	-1%	4%



**Table B-30
T5 Light Usage (Premise)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	100%	6	100%	100%
	Geo	100%	1	100%	100%
	Non-Geo	100%	5	100%	100%
Task	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Exit	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Display	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Other	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Unknown	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%

**Table B-31
Standard T8 Light Usage (Premise)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	98%	25	97%	100%
	Geo	100%	8	100%	100%
	Non-Geo	97%	17	94%	100%
Task	All Industrial	1%	25	0%	2%
	Geo	0%	8	0%	0%
	Non-Geo	1%	17	0%	3%
Exit	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	0%
Display	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	0%
Other	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	0%
Unknown	All Industrial	1%	25	0%	2%
	Geo	0%	8	0%	0%
	Non-Geo	2%	17	-1%	4%



**Table B-32
High Performance T8 Light Usage (Premise)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	100%	4	100%	100%
	Geo	100%	2	100%	100%
	Non-Geo	100%	2	100%	100%
Task	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Exit	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Display	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Unknown	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%

**Table B-33
Unknown T8 Light Usage (Premise)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	95%	3	88%	103%
	Geo	79%	2	47%	110%
	Non-Geo	100%	1	100%	100%
Task	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Exit	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Display	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Other	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Unknown	All Industrial	5%	3	-3%	12%
	Geo	21%	2	-10%	53%
	Non-Geo	0%	1	0%	0%



**Table B-34
T12 Light Usage (Premise)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	99%	18	97%	100%
	Geo	100%	5	99%	100%
	Non-Geo	99%	13	97%	101%
Task	All Industrial	0%	18	0%	0%
	Geo	0%	5	0%	1%
	Non-Geo	0%	13	0%	0%
Exit	All Industrial	0%	18	0%	0%
	Geo	0%	5	0%	0%
	Non-Geo	0%	13	0%	0%
Display	All Industrial	0%	18	0%	0%
	Geo	0%	5	0%	0%
	Non-Geo	0%	13	0%	0%
Other	All Industrial	0%	18	0%	0%
	Geo	0%	5	0%	0%
	Non-Geo	0%	13	0%	0%
Unknown	All Industrial	1%	18	0%	3%
	Geo	0%	5	0%	0%
	Non-Geo	1%	13	-1%	3%

**Table B-35
Unknown Fluorescent Tube Light Usage (Premise)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	100%	4	100%	100%
	Geo	100%	1	100%	100%
	Non-Geo	100%	3	100%	100%
Task	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Exit	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Display	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Unknown	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%



**Table B-36
Other Fluorescent Light Usage (Premise)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	#N/A	#N/A	#N/A	#N/A
	Geo	#N/A	#N/A	#N/A	#N/A
	Non-Geo	#N/A	#N/A	#N/A	#N/A
Task	All Industrial	#N/A	#N/A	#N/A	#N/A
	Geo	#N/A	#N/A	#N/A	#N/A
	Non-Geo	#N/A	#N/A	#N/A	#N/A
Exit	All Industrial	#N/A	#N/A	#N/A	#N/A
	Geo	#N/A	#N/A	#N/A	#N/A
	Non-Geo	#N/A	#N/A	#N/A	#N/A
Display	All Industrial	#N/A	#N/A	#N/A	#N/A
	Geo	#N/A	#N/A	#N/A	#N/A
	Non-Geo	#N/A	#N/A	#N/A	#N/A
Other	All Industrial	#N/A	#N/A	#N/A	#N/A
	Geo	#N/A	#N/A	#N/A	#N/A
	Non-Geo	#N/A	#N/A	#N/A	#N/A
Unknown	All Industrial	#N/A	#N/A	#N/A	#N/A
	Geo	#N/A	#N/A	#N/A	#N/A
	Non-Geo	#N/A	#N/A	#N/A	#N/A

**Table B-37
Other Light Usage (Premise)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	51%	7	15%	88%
	Geo	0%	4	0%	0%
	Non-Geo	69%	3	34%	105%
Task	All Industrial	0%	7	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	3	0%	0%
Exit	All Industrial	49%	7	12%	85%
	Geo	100%	4	100%	100%
	Non-Geo	31%	3	-5%	66%
Display	All Industrial	0%	7	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	3	0%	0%
Other	All Industrial	0%	7	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	3	0%	0%
Unknown	All Industrial	0%	7	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	3	0%	0%



**Table B-38
Quartz Light Usage (Premise)**

Usage	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Area	All Industrial	49%	3	6%	92%
	Geo	100%	1	100%	100%
	Non-Geo	0%	2	0%	0%
Task	All Industrial	51%	3	8%	94%
	Geo	0%	1	0%	0%
	Non-Geo	100%	2	100%	100%
Exit	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Display	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Other	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Unknown	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%



B.4. Ballast Types

B.4.1. Facility kWh Weighted Results

Table B-39
Overall Light Ballast Types (Facility kWh)

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	13%	35	6%	19%
	Geo	19%	11	6%	32%
	Non-Geo	10%	24	2%	17%
Energy Saving Magnetic	All Industrial	1%	35	0%	3%
	Geo	4%	11	-1%	9%
	Non-Geo	0%	24	0%	0%
Electronic	All Industrial	57%	35	42%	71%
	Geo	52%	11	27%	77%
	Non-Geo	59%	24	42%	77%
Other	All Industrial	0%	35	0%	1%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	1%
No Ballast	All Industrial	29%	35	15%	43%
	Geo	25%	11	2%	49%
	Non-Geo	30%	24	13%	48%
Unknown	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%



**Table B-40
HID Light Ballast Types (Facility kWh)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	39%	13	12%	65%
	Geo	87%	3	68%	106%
	Non-Geo	7%	10	0%	14%
Energy Saving Magnetic	All Industrial	0%	13	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	10	0%	0%
Electronic	All Industrial	2%	13	-1%	6%
	Geo	0%	3	0%	0%
	Non-Geo	4%	10	-1%	9%
Other	All Industrial	3%	13	-1%	8%
	Geo	0%	3	0%	0%
	Non-Geo	5%	10	-2%	13%
No Ballast	All Industrial	56%	13	30%	81%
	Geo	13%	3	-6%	32%
	Non-Geo	83%	10	71%	96%
Unknown	All Industrial	0%	13	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	10	0%	0%

**Table B-41
T5 Light Ballast Types (Facility kWh)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Energy Saving Magnetic	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Electronic	All Industrial	67%	6	40%	94%
	Geo	100%	1	100%	100%
	Non-Geo	61%	5	30%	92%
Other	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
No Ballast	All Industrial	33%	6	6%	60%
	Geo	0%	1	0%	0%
	Non-Geo	39%	5	8%	70%
Unknown	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%



**Table B-42
Standard T8 Light Ballast Types (Facility kWh)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	1%
	Non-Geo	0%	17	0%	0%
Energy Saving Magnetic	All Industrial	0%	25	0%	1%
	Geo	0%	8	0%	1%
	Non-Geo	0%	17	0%	0%
Electronic	All Industrial	60%	25	35%	84%
	Geo	65%	8	26%	104%
	Non-Geo	56%	17	27%	86%
Other	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	0%
No Ballast	All Industrial	40%	25	16%	64%
	Geo	34%	8	-5%	73%
	Non-Geo	44%	17	14%	73%
Unknown	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	0%

**Table B-43
High Performance T8 Light Ballast Types (Facility kWh)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Energy Saving Magnetic	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Electronic	All Industrial	100%	4	100%	100%
	Geo	100%	2	100%	100%
	Non-Geo	100%	2	100%	100%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
No Ballast	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Unknown	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%



**Table B-44
Unknown T8 Light Ballast Types (Facility kWh)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Energy Saving Magnetic	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Electronic	All Industrial	100%	3	100%	100%
	Geo	100%	2	100%	100%
	Non-Geo	100%	1	100%	100%
Other	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
No Ballast	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Unknown	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%

**Table B-45
T12 Light Ballast Types (Facility kWh)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	62%	18	39%	85%
	Geo	75%	5	46%	104%
	Non-Geo	57%	13	27%	87%
Energy Saving Magnetic	All Industrial	8%	18	-2%	18%
	Geo	25%	5	-4%	54%
	Non-Geo	1%	13	0%	1%
Electronic	All Industrial	24%	18	1%	47%
	Geo	0%	5	0%	0%
	Non-Geo	34%	13	4%	65%
Other	All Industrial	0%	18	0%	0%
	Geo	0%	5	0%	0%
	Non-Geo	0%	13	0%	0%
No Ballast	All Industrial	6%	18	1%	11%
	Geo	0%	5	0%	0%
	Non-Geo	8%	13	1%	16%
Unknown	All Industrial	0%	18	0%	0%
	Geo	0%	5	0%	0%
	Non-Geo	0%	13	0%	0%



**Table B-46
Other Fluorescent Light Ballast Types (Facility kWh)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Energy Saving Magnetic	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Electronic	All Industrial	100%	4	100%	100%
	Geo	100%	2	100%	100%
	Non-Geo	100%	2	100%	100%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
No Ballast	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Unknown	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%

B.4.2. Premise Weighted Results

**Table B-47
Overall Light Ballast Types (Premise)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	12%	35	4%	20%
	Geo	8%	11	-1%	16%
	Non-Geo	15%	24	5%	25%
Energy Saving Magnetic	All Industrial	0%	35	0%	1%
	Geo	0%	11	0%	1%
	Non-Geo	1%	24	0%	1%
Electronic	All Industrial	49%	35	30%	68%
	Geo	24%	11	-1%	48%
	Non-Geo	64%	24	52%	77%
Other	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
No Ballast	All Industrial	38%	35	15%	61%
	Geo	69%	11	38%	99%
	Non-Geo	20%	24	9%	31%
Unknown	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%



**Table B-48
HID Light Ballast Types (Premise)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	40%	13	18%	62%
	Geo	86%	3	65%	106%
	Non-Geo	32%	10	9%	56%
Energy Saving Magnetic	All Industrial	0%	13	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	10	0%	0%
Electronic	All Industrial	1%	13	0%	3%
	Geo	0%	3	0%	0%
	Non-Geo	2%	10	-1%	4%
Other	All Industrial	2%	13	-1%	5%
	Geo	0%	3	0%	0%
	Non-Geo	3%	10	-1%	6%
No Ballast	All Industrial	56%	13	34%	78%
	Geo	14%	3	-6%	35%
	Non-Geo	63%	10	40%	87%
Unknown	All Industrial	0%	13	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	10	0%	0%

**Table B-49
T5 Light Ballast Types (Premise)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Energy Saving Magnetic	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Electronic	All Industrial	63%	6	31%	94%
	Geo	100%	1	100%	100%
	Non-Geo	59%	5	25%	93%
Other	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
No Ballast	All Industrial	37%	6	6%	69%
	Geo	0%	1	0%	0%
	Non-Geo	41%	5	7%	75%
Unknown	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%



**Table B-50
Standard T8 Light Ballast Types (Premise)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	0%
Energy Saving Magnetic	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	1%
Electronic	All Industrial	62%	25	31%	93%
	Geo	25%	8	-6%	56%
	Non-Geo	94%	17	88%	99%
Other	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	0%
No Ballast	All Industrial	38%	25	7%	69%
	Geo	75%	8	44%	106%
	Non-Geo	6%	17	0%	11%
Unknown	All Industrial	0%	25	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	17	0%	0%

**Table B-51
High Performance T8 Light Ballast Types (Premise)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Energy Saving Magnetic	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Electronic	All Industrial	100%	4	100%	100%
	Geo	100%	2	100%	100%
	Non-Geo	100%	2	100%	100%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
No Ballast	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Unknown	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%



**Table B-52
Unknown T8 Light Ballast Types (Premise)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Energy Saving Magnetic	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Electronic	All Industrial	100%	3	100%	100%
	Geo	100%	2	100%	100%
	Non-Geo	100%	1	100%	100%
Other	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
No Ballast	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%
Unknown	All Industrial	0%	3	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	1	0%	0%

**Table B-53
T12 Light Ballast Types (Premise)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	66%	18	43%	89%
	Geo	97%	5	91%	102%
	Non-Geo	61%	13	33%	88%
Energy Saving Magnetic	All Industrial	2%	18	0%	4%
	Geo	3%	5	-2%	9%
	Non-Geo	2%	13	-1%	4%
Electronic	All Industrial	18%	18	-2%	39%
	Geo	0%	5	0%	0%
	Non-Geo	22%	13	-2%	45%
Other	All Industrial	0%	18	0%	0%
	Geo	0%	5	0%	0%
	Non-Geo	0%	13	0%	0%
No Ballast	All Industrial	14%	18	2%	26%
	Geo	0%	5	0%	0%
	Non-Geo	16%	13	1%	31%
Unknown	All Industrial	0%	18	0%	0%
	Geo	0%	5	0%	0%
	Non-Geo	0%	13	0%	0%



**Table B-54
Other Fluorescent Light Ballast Types (Premise)**

Ballast Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Standard Magnetic	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Energy Saving Magnetic	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Electronic	All Industrial	100%	4	100%	100%
	Geo	100%	2	100%	100%
	Non-Geo	100%	2	100%	100%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
No Ballast	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Unknown	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%



B.5. Control Types

B.5.1. Facility kWh Weighted Results

Table B-55
Overall Light Control Types (Facility kWh)

Control Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Manual On/Off Switch	All Industrial	97%	35	95%	98%
	Geo	95%	11	91%	99%
	Non-Geo	97%	24	96%	99%
Dimmer	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
Motion/Occupancy Sensor	All Industrial	2%	35	1%	3%
	Geo	4%	11	0%	7%
	Non-Geo	1%	24	0%	2%
Photocell	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
Timeclock	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
Photocell/Timeclock	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
Photocell with Dimming	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
EMS	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
None/Continuous	All Industrial	1%	35	0%	1%
	Geo	1%	11	0%	2%
	Non-Geo	0%	24	0%	1%
Other	All Industrial	1%	35	0%	2%
	Geo	0%	11	0%	0%
	Non-Geo	1%	24	0%	2%
Unknown	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%



B.5.2. Premise Weighted Results

Table B-56
Overall Light Control Types (Premise)

Control Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Manual On/Off Switch	All Industrial	97%	35	96%	99%
	Geo	97%	11	94%	101%
	Non-Geo	97%	24	96%	99%
Dimmer	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
Motion/Occupancy Sensor	All Industrial	1%	35	0%	2%
	Geo	2%	11	-1%	5%
	Non-Geo	0%	24	0%	0%
Photocell	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
Timeclock	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
Photocell/Timeclock	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
Photocell with Dimming	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
EMS	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%
None/Continuous	All Industrial	1%	35	0%	1%
	Geo	1%	11	0%	1%
	Non-Geo	0%	24	0%	1%
Other	All Industrial	1%	35	0%	2%
	Geo	0%	11	0%	0%
	Non-Geo	2%	24	0%	4%
Unknown	All Industrial	0%	35	0%	0%
	Geo	0%	11	0%	0%
	Non-Geo	0%	24	0%	0%



B.6. Energy Efficient Opportunities

B.6.1. Facility kWh Weighted Results

**Table B-57
Overall EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	17%	43	3%	31%
	Geo	21%	13	-2%	44%
	Non-Geo	16%	30	-1%	33%
Switch to Standard T8	All Industrial	14%	43	6%	21%
	Geo	21%	13	-2%	44%
	Non-Geo	12%	30	4%	19%
Switch to High Performance T8	All Industrial	54%	43	40%	68%
	Geo	76%	13	58%	94%
	Non-Geo	48%	30	32%	63%
Switch to T5	All Industrial	21%	43	12%	30%
	Geo	35%	13	12%	57%
	Non-Geo	17%	30	8%	26%
Switch to Pulse Start Metal Halide	All Industrial	6%	43	1%	10%
	Geo	0%	13	0%	0%
	Non-Geo	7%	30	2%	13%
Replace Ballasts for Automatic Daylighting	All Industrial	19%	43	9%	28%
	Geo	28%	13	8%	48%
	Non-Geo	16%	30	6%	26%
Occupancy Sensors	All Industrial	49%	43	36%	63%
	Geo	76%	13	58%	94%
	Non-Geo	42%	30	27%	57%
Dimmers	All Industrial	10%	43	4%	16%
	Geo	15%	13	-3%	32%
	Non-Geo	9%	30	3%	15%
Other Controls	All Industrial	2%	43	-1%	4%
	Geo	8%	13	-2%	19%
	Non-Geo	0%	30	0%	0%
Other	All Industrial	3%	43	0%	6%
	Geo	0%	13	0%	0%
	Non-Geo	4%	30	0%	8%



**Table B-58
Incandescent EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	75%	5	50%	100%
	Geo	89%	2	71%	107%
	Non-Geo	70%	3	37%	104%
Switch to Standard T8	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Switch to High Performance T8	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Switch to T5	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Occupancy Sensors	All Industrial	21%	5	-6%	47%
	Geo	89%	2	71%	107%
	Non-Geo	0%	3	0%	0%
Dimmers	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Other Controls	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Other	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%



**Table B-59
CFL EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to Standard T8	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to High Performance T8	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to T5	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Occupancy Sensors	All Industrial	21%	6	-3%	45%
	Geo	0%	1	0%	0%
	Non-Geo	28%	5	-2%	57%
Dimmers	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Other Controls	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Other	All Industrial	18%	6	-4%	40%
	Geo	0%	1	0%	0%
	Non-Geo	24%	5	-3%	51%



**Table B-60
HID EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	18	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	14	0%	0%
Switch to Standard T8	All Industrial	4%	18	-1%	10%
	Geo	0%	4	0%	0%
	Non-Geo	5%	14	-2%	12%
Switch to High Performance T8	All Industrial	20%	18	4%	35%
	Geo	33%	4	-3%	69%
	Non-Geo	17%	14	1%	34%
Switch to T5	All Industrial	11%	18	3%	19%
	Geo	19%	4	-2%	39%
	Non-Geo	10%	14	1%	19%
Switch to Pulse Start Metal Halide	All Industrial	5%	18	-2%	12%
	Geo	0%	4	0%	0%
	Non-Geo	6%	14	-2%	15%
Replace Ballasts for Automatic Daylighting	All Industrial	11%	18	-3%	24%
	Geo	0%	4	0%	0%
	Non-Geo	13%	14	-3%	28%
Occupancy Sensors	All Industrial	27%	18	10%	44%
	Geo	51%	4	11%	91%
	Non-Geo	23%	14	5%	41%
Dimmers	All Industrial	3%	18	0%	6%
	Geo	0%	4	0%	0%
	Non-Geo	4%	14	0%	7%
Other Controls	All Industrial	0%	18	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	14	0%	0%
Other	All Industrial	5%	18	-2%	12%
	Geo	0%	4	0%	0%
	Non-Geo	6%	14	-2%	15%



**Table B-61
T5 EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to Standard T8	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to High Performance T8	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to T5	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	6%	7	-2%	14%
	Geo	0%	2	0%	0%
	Non-Geo	8%	5	-3%	18%
Occupancy Sensors	All Industrial	36%	7	6%	65%
	Geo	0%	2	0%	0%
	Non-Geo	46%	5	12%	79%
Dimmers	All Industrial	6%	7	-2%	14%
	Geo	0%	2	0%	0%
	Non-Geo	8%	5	-3%	18%
Other Controls	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Other	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%



**Table B-62
St T8 EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	27	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	19	0%	0%
Switch to Standard T8	All Industrial	0%	27	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	19	0%	0%
Switch to High Performance T8	All Industrial	79%	27	64%	95%
	Geo	88%	8	74%	103%
	Non-Geo	76%	19	56%	95%
Switch to T5	All Industrial	17%	27	5%	28%
	Geo	29%	8	-1%	58%
	Non-Geo	12%	19	3%	22%
Switch to Pulse Start Metal Halide	All Industrial	2%	27	-1%	6%
	Geo	0%	8	0%	0%
	Non-Geo	3%	19	-1%	8%
Replace Ballasts for Automatic Daylighting	All Industrial	22%	27	9%	35%
	Geo	25%	8	1%	49%
	Non-Geo	21%	19	6%	36%
Occupancy Sensors	All Industrial	63%	27	46%	79%
	Geo	58%	8	29%	86%
	Non-Geo	65%	19	45%	84%
Dimmers	All Industrial	16%	27	6%	26%
	Geo	20%	8	-3%	43%
	Non-Geo	14%	19	4%	24%
Other Controls	All Industrial	3%	27	-1%	7%
	Geo	12%	8	-3%	26%
	Non-Geo	0%	19	0%	0%
Other	All Industrial	1%	27	0%	2%
	Geo	0%	8	0%	0%
	Non-Geo	1%	19	0%	3%



**Table B-63
High Performance T8 EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to Standard T8	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to High Performance T8	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to T5	All Industrial	25%	4	-4%	54%
	Geo	69%	2	29%	109%
	Non-Geo	0%	2	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Occupancy Sensors	All Industrial	50%	4	15%	86%
	Geo	69%	2	29%	109%
	Non-Geo	40%	2	-5%	85%
Dimmers	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Other Controls	All Industrial	25%	4	-4%	54%
	Geo	69%	2	29%	109%
	Non-Geo	0%	2	0%	0%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%



**Table B-64
Unknown T8 EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Switch to Standard T8	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Switch to High Performance T8	All Industrial	9%	7	-1%	19%
	Geo	17%	3	-7%	42%
	Non-Geo	7%	4	-3%	18%
Switch to T5	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Occupancy Sensors	All Industrial	9%	7	-1%	19%
	Geo	17%	3	-7%	42%
	Non-Geo	7%	4	-3%	18%
Dimmers	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Other Controls	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Other	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%



**Table B-65
T12 EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	22	0%	0%
	Geo	0%	7	0%	0%
	Non-Geo	0%	15	0%	0%
Switch to Standard T8	All Industrial	14%	22	4%	23%
	Geo	0%	7	0%	0%
	Non-Geo	17%	15	5%	30%
Switch to High Performance T8	All Industrial	57%	22	36%	78%
	Geo	66%	7	37%	95%
	Non-Geo	55%	15	30%	80%
Switch to T5	All Industrial	20%	22	8%	32%
	Geo	16%	7	-4%	37%
	Non-Geo	21%	15	7%	35%
Switch to Pulse Start Metal Halide	All Industrial	4%	22	-1%	9%
	Geo	0%	7	0%	0%
	Non-Geo	5%	15	-2%	11%
Replace Ballasts for Automatic Daylighting	All Industrial	12%	22	2%	22%
	Geo	19%	7	-4%	41%
	Non-Geo	10%	15	0%	21%
Occupancy Sensors	All Industrial	45%	22	26%	64%
	Geo	66%	7	37%	95%
	Non-Geo	39%	15	17%	61%
Dimmers	All Industrial	2%	22	-1%	6%
	Geo	0%	7	0%	0%
	Non-Geo	3%	15	-1%	7%
Other Controls	All Industrial	4%	22	-1%	8%
	Geo	16%	7	-4%	37%
	Non-Geo	0%	15	0%	0%
Other	All Industrial	0%	22	0%	0%
	Geo	0%	7	0%	0%
	Non-Geo	0%	15	0%	0%



**Table B-66
Unknown Fluorescent Tube EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Switch to Standard T8	All Industrial	63%	4	27%	98%
	Geo	100%	1	100%	100%
	Non-Geo	16%	3	-6%	37%
Switch to High Performance T8	All Industrial	87%	4	68%	105%
	Geo	100%	1	100%	100%
	Non-Geo	69%	3	33%	105%
Switch to T5	All Industrial	63%	4	27%	98%
	Geo	100%	1	100%	100%
	Non-Geo	16%	3	-6%	37%
Switch to Pulse Start Metal Halide	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Occupancy Sensors	All Industrial	24%	4	-6%	53%
	Geo	0%	1	0%	0%
	Non-Geo	54%	3	13%	94%
Dimmers	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Other Controls	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%



**Table B-67
Other Fluorescent EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to Standard T8	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to High Performance T8	All Industrial	12%	4	-4%	29%
	Geo	0%	2	0%	0%
	Non-Geo	22%	2	-10%	54%
Switch to T5	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	28%	4	-4%	60%
	Geo	63%	2	20%	107%
	Non-Geo	0%	2	0%	0%
Occupancy Sensors	All Industrial	57%	4	19%	95%
	Geo	100%	2	100%	100%
	Non-Geo	22%	2	-10%	54%
Dimmers	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Other Controls	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%



**Table B-68
Other Light Type EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Switch to Standard T8	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Switch to High Performance T8	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Switch to T5	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Occupancy Sensors	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Dimmers	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Other Controls	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Other	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%



**Table B-69
Quartz EE Opportunities (Facility kWh)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	25%	3	-7%	57%
	Geo	0%	1	0%	0%
	Non-Geo	62%	2	19%	106%
Switch to Standard T8	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to High Performance T8	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to T5	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Occupancy Sensors	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Dimmers	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Other Controls	All Industrial	60%	3	21%	99%
	Geo	100%	1	100%	100%
	Non-Geo	0%	2	0%	0%
Other	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%



B.6.2. Premise Weighted Results

**Table B-70
Overall EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	15%	43	-1%	31%
	Geo	69%	13	38%	99%
	Non-Geo	2%	30	0%	5%
Switch to Standard T8	All Industrial	33%	43	13%	53%
	Geo	69%	13	38%	99%
	Non-Geo	24%	30	4%	45%
Switch to High Performance T8	All Industrial	78%	43	61%	95%
	Geo	97%	13	95%	100%
	Non-Geo	73%	30	53%	93%
Switch to T5	All Industrial	37%	43	17%	58%
	Geo	76%	13	52%	101%
	Non-Geo	28%	30	8%	49%
Switch to Pulse Start Metal Halide	All Industrial	3%	43	0%	6%
	Geo	0%	13	0%	0%
	Non-Geo	4%	30	0%	7%
Replace Ballasts for Automatic Daylighting	All Industrial	36%	43	16%	57%
	Geo	8%	13	-3%	19%
	Non-Geo	43%	30	19%	67%
Occupancy Sensors	All Industrial	74%	43	56%	91%
	Geo	97%	13	95%	100%
	Non-Geo	68%	30	47%	89%
Dimmers	All Industrial	8%	43	3%	13%
	Geo	7%	13	-4%	17%
	Non-Geo	9%	30	3%	14%
Other Controls	All Industrial	1%	43	0%	3%
	Geo	7%	13	-4%	17%
	Non-Geo	0%	30	0%	0%
Other	All Industrial	3%	43	0%	5%
	Geo	0%	13	0%	0%
	Non-Geo	3%	30	0%	6%



**Table B-71
Incandescent EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	88%	5	71%	105%
	Geo	99%	2	97%	101%
	Non-Geo	20%	3	-7%	47%
Switch to Standard T8	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Switch to High Performance T8	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Switch to T5	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Occupancy Sensors	All Industrial	85%	5	66%	105%
	Geo	99%	2	97%	101%
	Non-Geo	0%	3	0%	0%
Dimmers	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Other Controls	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%
Other	All Industrial	0%	5	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	3	0%	0%



**Table B-72
CFL EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to Standard T8	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to High Performance T8	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to T5	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Occupancy Sensors	All Industrial	80%	6	56%	104%
	Geo	0%	1	0%	0%
	Non-Geo	80%	5	57%	104%
Dimmers	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Other Controls	All Industrial	0%	6	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	5	0%	0%
Other	All Industrial	7%	6	-4%	19%
	Geo	0%	1	0%	0%
	Non-Geo	7%	5	-5%	19%



**Table B-73
HID EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	18	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	14	0%	0%
Switch to Standard T8	All Industrial	1%	18	-1%	3%
	Geo	0%	4	0%	0%
	Non-Geo	1%	14	-1%	3%
Switch to High Performance T8	All Industrial	41%	18	6%	75%
	Geo	25%	4	-4%	54%
	Non-Geo	41%	14	6%	76%
Switch to T5	All Industrial	6%	18	0%	12%
	Geo	50%	4	17%	83%
	Non-Geo	6%	14	0%	12%
Switch to Pulse Start Metal Halide	All Industrial	3%	18	-1%	8%
	Geo	0%	4	0%	0%
	Non-Geo	3%	14	-2%	8%
Replace Ballasts for Automatic Daylighting	All Industrial	36%	18	1%	71%
	Geo	0%	4	0%	0%
	Non-Geo	37%	14	1%	72%
Occupancy Sensors	All Industrial	43%	18	8%	77%
	Geo	75%	4	46%	104%
	Non-Geo	42%	14	7%	77%
Dimmers	All Industrial	7%	18	-1%	14%
	Geo	0%	4	0%	0%
	Non-Geo	7%	14	-1%	14%
Other Controls	All Industrial	0%	18	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	14	0%	0%
Other	All Industrial	3%	18	-1%	8%
	Geo	0%	4	0%	0%
	Non-Geo	3%	14	-2%	8%



**Table B-74
T5 EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to Standard T8	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to High Performance T8	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to T5	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	7%	7	-4%	17%
	Geo	0%	2	0%	0%
	Non-Geo	7%	5	-4%	18%
Occupancy Sensors	All Industrial	78%	7	54%	102%
	Geo	0%	2	0%	0%
	Non-Geo	84%	5	64%	104%
Dimmers	All Industrial	7%	7	-4%	17%
	Geo	0%	2	0%	0%
	Non-Geo	7%	5	-4%	18%
Other Controls	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%
Other	All Industrial	0%	7	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	5	0%	0%



**Table B-75
St T8 EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	27	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	19	0%	0%
Switch to Standard T8	All Industrial	0%	27	0%	0%
	Geo	0%	8	0%	0%
	Non-Geo	0%	19	0%	0%
Switch to High Performance T8	All Industrial	95%	27	90%	99%
	Geo	93%	8	83%	104%
	Non-Geo	95%	19	90%	100%
Switch to T5	All Industrial	25%	27	2%	48%
	Geo	71%	8	41%	101%
	Non-Geo	7%	19	0%	13%
Switch to Pulse Start Metal Halide	All Industrial	1%	27	0%	2%
	Geo	0%	8	0%	0%
	Non-Geo	1%	19	0%	2%
Replace Ballasts for Automatic Daylighting	All Industrial	33%	27	8%	57%
	Geo	7%	8	-3%	18%
	Non-Geo	43%	19	13%	73%
Occupancy Sensors	All Industrial	68%	27	44%	91%
	Geo	22%	8	-2%	45%
	Non-Geo	87%	19	76%	97%
Dimmers	All Industrial	9%	27	2%	15%
	Geo	7%	8	-4%	17%
	Non-Geo	10%	19	1%	18%
Other Controls	All Industrial	2%	27	-1%	5%
	Geo	7%	8	-4%	17%
	Non-Geo	0%	19	0%	0%
Other	All Industrial	2%	27	-1%	5%
	Geo	0%	8	0%	0%
	Non-Geo	3%	19	-1%	7%



**Table B-76
High Performance T8 EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to Standard T8	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to High Performance T8	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to T5	All Industrial	40%	4	1%	80%
	Geo	91%	2	76%	106%
	Non-Geo	0%	2	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Occupancy Sensors	All Industrial	82%	4	61%	103%
	Geo	91%	2	76%	106%
	Non-Geo	75%	2	40%	110%
Dimmers	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Other Controls	All Industrial	40%	4	1%	80%
	Geo	91%	2	76%	106%
	Non-Geo	0%	2	0%	0%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%



**Table B-77
Unknown T8 EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Switch to Standard T8	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Switch to High Performance T8	All Industrial	9%	7	-5%	22%
	Geo	33%	3	-2%	69%
	Non-Geo	8%	4	-5%	21%
Switch to T5	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Occupancy Sensors	All Industrial	9%	7	-5%	22%
	Geo	33%	3	-2%	69%
	Non-Geo	8%	4	-5%	21%
Dimmers	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Other Controls	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%
Other	All Industrial	0%	7	0%	0%
	Geo	0%	3	0%	0%
	Non-Geo	0%	4	0%	0%



**Table B-78
T12 EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	22	0%	0%
	Geo	0%	7	0%	0%
	Non-Geo	0%	15	0%	0%
Switch to Standard T8	All Industrial	34%	22	7%	61%
	Geo	0%	7	0%	0%
	Non-Geo	36%	15	7%	65%
Switch to High Performance T8	All Industrial	93%	22	88%	99%
	Geo	92%	7	83%	101%
	Non-Geo	94%	15	88%	99%
Switch to T5	All Industrial	37%	22	10%	64%
	Geo	40%	7	2%	79%
	Non-Geo	37%	15	8%	66%
Switch to Pulse Start Metal Halide	All Industrial	2%	22	-1%	6%
	Geo	0%	7	0%	0%
	Non-Geo	2%	15	-1%	6%
Replace Ballasts for Automatic Daylighting	All Industrial	27%	22	0%	55%
	Geo	4%	7	-2%	10%
	Non-Geo	29%	15	0%	57%
Occupancy Sensors	All Industrial	84%	22	72%	95%
	Geo	92%	7	83%	101%
	Non-Geo	83%	15	71%	95%
Dimmers	All Industrial	1%	22	0%	2%
	Geo	0%	7	0%	0%
	Non-Geo	1%	15	0%	2%
Other Controls	All Industrial	2%	22	-1%	5%
	Geo	40%	7	2%	79%
	Non-Geo	0%	15	0%	0%
Other	All Industrial	0%	22	0%	0%
	Geo	0%	7	0%	0%
	Non-Geo	0%	15	0%	0%



**Table B-79
Unknown Fluorescent Tube EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Switch to Standard T8	All Industrial	89%	4	74%	105%
	Geo	100%	1	100%	100%
	Non-Geo	43%	3	2%	84%
Switch to High Performance T8	All Industrial	92%	4	79%	105%
	Geo	100%	1	100%	100%
	Non-Geo	57%	3	16%	98%
Switch to T5	All Industrial	89%	4	74%	105%
	Geo	100%	1	100%	100%
	Non-Geo	43%	3	2%	84%
Switch to Pulse Start Metal Halide	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Occupancy Sensors	All Industrial	3%	4	-2%	7%
	Geo	0%	1	0%	0%
	Non-Geo	14%	3	-5%	34%
Dimmers	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Other Controls	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	3	0%	0%



**Table B-80
Other Fluorescent EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to Standard T8	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to High Performance T8	All Industrial	7%	4	-4%	19%
	Geo	0%	2	0%	0%
	Non-Geo	8%	2	-6%	23%
Switch to T5	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	7%	4	-4%	18%
	Geo	50%	2	3%	97%
	Non-Geo	0%	2	0%	0%
Occupancy Sensors	All Industrial	21%	4	-4%	47%
	Geo	100%	2	100%	100%
	Non-Geo	8%	2	-6%	23%
Dimmers	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Other Controls	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%
Other	All Industrial	0%	4	0%	0%
	Geo	0%	2	0%	0%
	Non-Geo	0%	2	0%	0%



**Table B-81
Other Light Type EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Switch to Standard T8	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Switch to High Performance T8	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Switch to T5	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Occupancy Sensors	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Dimmers	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Other Controls	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%
Other	All Industrial	0%	10	0%	0%
	Geo	0%	4	0%	0%
	Non-Geo	0%	6	0%	0%



**Table B-82
Quartz EE Opportunities (Premise)**

Energy Efficiency Opportunity	Area	Minimum Percent of Premises with Opportunity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Switch to CFL	All Industrial	34%	3	-2%	70%
	Geo	0%	1	0%	0%
	Non-Geo	50%	2	3%	97%
Switch to Standard T8	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to High Performance T8	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to T5	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Switch to Pulse Start Metal Halide	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Replace Ballasts for Automatic Daylighting	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Occupancy Sensors	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Dimmers	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%
Other Controls	All Industrial	33%	3	-3%	68%
	Geo	100%	1	100%	100%
	Non-Geo	0%	2	0%	0%
Other	All Industrial	0%	3	0%	0%
	Geo	0%	1	0%	0%
	Non-Geo	0%	2	0%	0%



Appendix C: Motors

C.1. Premise Weighted Results

C.1.1. Motor Details

**Table C-1
Motors by Size Category**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1-5 hp	All Industrial	62.8%	43	55.3%	70.3%
	Geo	68.3%	14	65.2%	71.3%
	Non-Geo	58.7%	29	47.5%	69.8%
6-20 hp	All Industrial	23.5%	43	18.5%	28.5%
	Geo	28.0%	14	26.0%	29.9%
	Non-Geo	20.2%	29	12.2%	28.2%
21-50 hp	All Industrial	5.0%	43	2.1%	7.8%
	Geo	1.4%	14	-0.3%	3.0%
	Non-Geo	7.7%	29	4.5%	10.9%
51-100 hp	All Industrial	1.7%	43	1.2%	2.1%
	Geo	2.0%	14	1.6%	2.3%
	Non-Geo	1.5%	29	0.7%	2.2%
101-200 hp	All Industrial	0.5%	43	0.2%	0.8%
	Geo	0.3%	14	-0.1%	0.6%
	Non-Geo	0.7%	29	0.3%	1.1%
201-500 hp	All Industrial	0.1%	43	0.0%	0.2%
	Geo	0.1%	14	0.0%	0.2%
	Non-Geo	0.1%	29	0.0%	0.2%
501-1000 hp	All Industrial	0.0%	43	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.1%
	Non-Geo	0.0%	29	0.0%	0.0%
Greater than 1000 hp	All Industrial	0.0%	43	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.1%
	Non-Geo	0.0%	29	0.0%	0.0%



**Table C-2
Motor Horespower by Size Category**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1-5 hp	All Industrial	19.5%	43	15.2%	23.9%
	Geo	22.1%	14	15.2%	28.9%
	Non-Geo	17.9%	29	13.2%	22.7%
6-20 hp	All Industrial	33.3%	43	25.4%	41.3%
	Geo	40.9%	14	29.6%	52.2%
	Non-Geo	28.5%	29	19.8%	37.3%
21-50 hp	All Industrial	18.9%	43	10.8%	27.0%
	Geo	5.5%	14	-0.1%	11.2%
	Non-Geo	27.4%	29	19.4%	35.3%
51-100 hp	All Industrial	14.5%	43	10.9%	18.1%
	Geo	17.1%	14	13.0%	21.2%
	Non-Geo	12.8%	29	8.1%	17.6%
101-200 hp	All Industrial	8.4%	43	4.4%	12.4%
	Geo	4.6%	14	0.0%	9.2%
	Non-Geo	10.8%	29	5.9%	15.7%
201-500 hp	All Industrial	3.1%	43	0.8%	5.4%
	Geo	4.0%	14	-1.0%	9.0%
	Non-Geo	2.6%	29	-0.1%	5.2%
501-1000 hp	All Industrial	0.9%	43	-0.3%	2.2%
	Geo	2.4%	14	-1.3%	6.1%
	Non-Geo	0.0%	29	0.0%	0.0%
Greater than 1000 hp	All Industrial	1.3%	43	-0.4%	3.1%
	Geo	3.4%	14	-1.8%	8.6%
	Non-Geo	0.0%	29	0.0%	0.0%



**Table C-3
NEMA Motor HP as a Percent of Total Motor HP by Size Category**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
ALL	All Industrial	10.3%	29	1.1%	19.5%
	Geo	1.8%	14	-0.2%	3.8%
	Non-Geo	7.0%	43	0.9%	13.1%
1-5 hp	All Industrial	0.5%	29	0.2%	0.9%
	Geo	0.2%	14	-0.1%	0.6%
	Non-Geo	0.4%	43	0.2%	0.7%
6-20 hp	All Industrial	2.5%	29	0.6%	4.3%
	Geo	0.3%	14	-0.1%	0.7%
	Non-Geo	1.7%	43	0.4%	2.9%
21-50 hp	All Industrial	6.8%	29	-0.7%	14.2%
	Geo	0.3%	14	0.0%	0.5%
	Non-Geo	4.2%	43	-0.6%	9.0%
51-100 hp	All Industrial	0.1%	29	0.0%	0.3%
	Geo	0.7%	14	-0.3%	1.8%
	Non-Geo	0.4%	43	0.0%	0.7%
101-200 hp	All Industrial	0.4%	29	-0.1%	0.9%
	Geo	0.2%	14	-0.2%	0.7%
	Non-Geo	0.3%	43	0.0%	0.7%
201-500 hp	All Industrial	0.0%	29	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	0.0%	43	0.0%	0.0%
501-1000 hp	All Industrial	0.0%	29	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	0.0%	43	0.0%	0.0%
Greater than 1000 hp	All Industrial	0.0%	29	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	0.0%	43	0.0%	0.0%



**Table C-4
NEMA Motor HP as a Percent of Size Category HP**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1-5 hp	All Industrial	3.7%	36	1.7%	5.8%
	Geo	5.8%	12	-0.2%	11.9%
	Non-Geo	3.4%	24	1.2%	5.6%
6-20 hp	All Industrial	12.5%	34	3.2%	21.7%
	Geo	3.8%	12	0.7%	6.9%
	Non-Geo	15.4%	22	2.6%	28.3%
21-50 hp	All Industrial	27.4%	30	6.1%	48.7%
	Geo	4.6%	10	1.3%	7.9%
	Non-Geo	31.0%	20	7.4%	54.7%
51-100 hp	All Industrial	2.9%	16	-0.3%	6.0%
	Geo	4.3%	9	-2.7%	11.3%
	Non-Geo	1.4%	7	-0.9%	3.6%
101-200 hp	All Industrial	4.9%	14	-0.5%	10.3%
	Geo	5.3%	8	-3.1%	13.8%
	Non-Geo	4.7%	6	-3.0%	12.5%
201-500 hp	All Industrial	0.0%	5	0.0%	0.0%
	Geo	0.0%	3	0.0%	0.0%
	Non-Geo	0.0%	2	0.0%	0.0%
501-1000 hp	All Industrial	0.0%	1	.	.
	Geo	0.0%	1	.	.
	Non-Geo	0.0%	0	0.0%	0.0%
Greater than 1000 hp	All Industrial	0.0%	1	.	.
	Geo	0.0%	1	.	.
	Non-Geo	0.0%	0	0.0%	0.0%



**Table C-5
NEMA Motor HP by Size Category**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1-5 hp	All Industrial	5.9%	43	0.1%	11.8%
	Geo	13.1%	14	1.8%	24.4%
	Non-Geo	5.1%	29	-0.7%	11.0%
6-20 hp	All Industrial	23.6%	43	18.3%	28.9%
	Geo	18.4%	14	8.4%	28.5%
	Non-Geo	24.2%	29	17.9%	30.4%
21-50 hp	All Industrial	60.4%	43	41.8%	79.0%
	Geo	14.1%	14	9.0%	19.1%
	Non-Geo	65.5%	29	49.4%	81.7%
51-100 hp	All Industrial	5.3%	43	-1.0%	11.6%
	Geo	40.7%	14	13.4%	68.0%
	Non-Geo	1.4%	29	-0.8%	3.5%
101-200 hp	All Industrial	4.8%	43	-1.3%	10.9%
	Geo	13.7%	14	-3.2%	30.5%
	Non-Geo	3.8%	29	-2.3%	9.8%
201-500 hp	All Industrial	0.0%	43	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	0.0%	29	0.0%	0.0%
501-1000 hp	All Industrial	0.0%	43	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	0.0%	29	0.0%	0.0%
Greater than 1000 hp	All Industrial	0.0%	43	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	0.0%	29	0.0%	0.0%



**Table C-6
Variable Load HP as a Percent of Total HP**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
ALL	All Industrial	40.6%	43	26.1%	55.0%
	Geo	66.0%	14	52.4%	79.6%
	Non-Geo	24.4%	29	15.7%	33.1%
1-5 hp	All Industrial	9.4%	43	3.0%	15.8%
	Geo	18.5%	14	9.0%	28.0%
	Non-Geo	3.6%	29	2.2%	5.0%
6-20 hp	All Industrial	18.7%	43	7.8%	29.6%
	Geo	34.8%	14	19.2%	50.4%
	Non-Geo	8.5%	29	4.5%	12.5%
21-50 hp	All Industrial	2.4%	43	1.3%	3.5%
	Geo	1.5%	14	-0.1%	3.1%
	Non-Geo	3.0%	29	1.8%	4.2%
51-100 hp	All Industrial	3.5%	43	1.2%	5.8%
	Geo	1.8%	14	0.2%	3.4%
	Non-Geo	4.6%	29	1.3%	8.0%
101-200 hp	All Industrial	2.5%	43	0.7%	4.4%
	Geo	2.1%	14	-0.5%	4.8%
	Non-Geo	2.8%	29	0.2%	5.4%
201-500 hp	All Industrial	1.7%	43	0.0%	3.5%
	Geo	1.4%	14	-0.8%	3.6%
	Non-Geo	1.9%	29	-0.6%	4.5%
501-1000 hp	All Industrial	0.9%	43	-0.3%	2.2%
	Geo	2.4%	14	-1.3%	6.1%
	Non-Geo	0.0%	29	0.0%	0.0%
Greater than 1000 hp	All Industrial	1.3%	43	-0.4%	3.1%
	Geo	3.4%	14	-1.8%	8.6%
	Non-Geo	0.0%	29	0.0%	0.0%



**Table C-7
Variable Load HP as a Percent of Size Category HP**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1-5 hp	All Industrial	50.7%	40	25.1%	76.3%
	Geo	87.4%	13	71.3%	103.5%
	Non-Geo	21.3%	27	15.5%	27.1%
6-20 hp	All Industrial	69.0%	37	49.0%	89.0%
	Geo	88.2%	13	73.0%	103.4%
	Non-Geo	44.1%	24	31.4%	56.7%
21-50 hp	All Industrial	14.9%	31	7.6%	22.2%
	Geo	41.7%	10	27.9%	55.5%
	Non-Geo	12.4%	21	5.4%	19.4%
51-100 hp	All Industrial	27.8%	18	7.6%	48.0%
	Geo	10.7%	10	-0.5%	21.8%
	Non-Geo	46.3%	8	15.3%	77.3%
101-200 hp	All Industrial	35.9%	16	14.8%	57.0%
	Geo	45.9%	8	12.7%	79.2%
	Non-Geo	32.5%	8	4.1%	60.8%
201-500 hp	All Industrial	63.2%	4	28.6%	97.7%
	Geo	35.4%	3	6.3%	64.6%
	Non-Geo	100.0%	1	.	.
501-1000 hp	All Industrial	100.0%	1	.	.
	Geo	100.0%	1	.	.
	Non-Geo	0.0%	0	0.0%	0.0%
Greater than 1000 hp	All Industrial	100.0%	1	.	.
	Geo	100.0%	1	.	.
	Non-Geo	0.0%	0	0.0%	0.0%



**Table C-8
Variable Load HP by Size Category**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1-5 hp	All Industrial	23.1%	43	14.3%	31.9%
	Geo	28.1%	14	18.6%	37.5%
	Non-Geo	14.7%	29	9.3%	20.0%
6-20 hp	All Industrial	46.2%	43	33.6%	58.7%
	Geo	52.8%	14	38.3%	67.2%
	Non-Geo	34.9%	29	24.3%	45.4%
21-50 hp	All Industrial	5.9%	43	1.8%	10.1%
	Geo	2.2%	14	-0.5%	5.0%
	Non-Geo	12.3%	29	7.4%	17.1%
51-100 hp	All Industrial	8.7%	43	1.8%	15.7%
	Geo	2.8%	14	-0.1%	5.6%
	Non-Geo	19.0%	29	9.7%	28.4%
101-200 hp	All Industrial	6.2%	43	0.7%	11.7%
	Geo	3.2%	14	-1.2%	7.6%
	Non-Geo	11.4%	29	1.5%	21.2%
201-500 hp	All Industrial	4.2%	43	-0.5%	9.0%
	Geo	2.1%	14	-1.4%	5.7%
	Non-Geo	7.8%	29	-1.9%	17.6%
501-1000 hp	All Industrial	2.3%	43	-0.9%	5.5%
	Geo	3.7%	14	-2.4%	9.7%
	Non-Geo	0.0%	29	0.0%	0.0%
Greater than 1000 hp	All Industrial	3.3%	43	-1.3%	7.8%
	Geo	5.1%	14	-3.3%	13.6%
	Non-Geo	0.0%	29	0.0%	0.0%



**Table C-9
VFD Motor HP as a Percent of Total HP**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
ALL	All Industrial	13.8%	43	5.7%	21.9%
	Geo	11.2%	14	-3.2%	25.7%
	Non-Geo	15.4%	29	6.1%	24.8%
1-5 hp	All Industrial	0.9%	43	0.4%	1.4%
	Geo	0.6%	14	-0.1%	1.4%
	Non-Geo	1.0%	29	0.4%	1.7%
6-20 hp	All Industrial	6.0%	43	1.6%	10.4%
	Geo	0.3%	14	0.0%	0.7%
	Non-Geo	9.6%	29	3.4%	15.7%
21-50 hp	All Industrial	1.6%	43	0.7%	2.5%
	Geo	1.5%	14	-0.5%	3.5%
	Non-Geo	1.7%	29	0.8%	2.6%
51-100 hp	All Industrial	2.0%	43	0.1%	3.9%
	Geo	0.1%	14	0.0%	0.3%
	Non-Geo	3.2%	29	0.4%	6.0%
101-200 hp	All Industrial	0.0%	43	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	0.0%	29	0.0%	0.0%
201-500 hp	All Industrial	1.1%	43	-0.4%	2.6%
	Geo	2.8%	14	-1.5%	7.2%
	Non-Geo	0.0%	29	0.0%	0.0%
501-1000 hp	All Industrial	0.9%	43	-0.3%	2.2%
	Geo	2.4%	14	-1.3%	6.1%
	Non-Geo	0.0%	29	0.0%	0.0%
Greater than 1000 hp	All Industrial	1.3%	43	-0.4%	3.1%
	Geo	3.4%	14	-1.8%	8.6%
	Non-Geo	0.0%	29	0.0%	0.0%



**Table C-10
VFD Motor HP as a Percent of Size Category HP**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1-5 hp	All Industrial	4.6%	41	1.4%	7.9%
	Geo	2.9%	14	-1.2%	7.0%
	Non-Geo	6.0%	27	1.9%	10.1%
6-20 hp	All Industrial	21.6%	38	3.3%	39.9%
	Geo	0.8%	14	-0.3%	1.8%
	Non-Geo	49.6%	24	27.4%	71.8%
21-50 hp	All Industrial	9.4%	31	3.5%	15.3%
	Geo	27.0%	11	0.5%	53.4%
	Non-Geo	6.9%	20	1.8%	11.9%
51-100 hp	All Industrial	15.7%	18	0.1%	31.3%
	Geo	0.8%	10	-0.4%	1.9%
	Non-Geo	31.9%	8	5.1%	58.6%
101-200 hp	All Industrial	0.0%	16	0.0%	0.0%
	Geo	0.0%	8	0.0%	0.0%
	Non-Geo	0.0%	8	0.0%	0.0%
201-500 hp	All Industrial	40.4%	4	-16.5%	97.3%
	Geo	70.9%	3	12.5%	129.3%
	Non-Geo	0.0%	1	.	.
501-1000 hp	All Industrial	100.0%	1	.	.
	Geo	100.0%	1	.	.
	Non-Geo	0.0%	0	0.0%	0.0%
Greater than 1000 hp	All Industrial	100.0%	1	.	.
	Geo	100.0%	1	.	.
	Non-Geo	0.0%	0	0.0%	0.0%



**Table C-11
VFD Motor HP by Size Category**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1-5 hp	All Industrial	6.3%	43	1.7%	10.9%
	Geo	5.7%	14	-1.5%	12.9%
	Non-Geo	6.6%	29	0.5%	12.7%
6-20 hp	All Industrial	43.3%	43	24.9%	61.7%
	Geo	2.8%	14	-0.5%	6.2%
	Non-Geo	62.0%	29	54.4%	69.6%
21-50 hp	All Industrial	11.5%	43	5.7%	17.4%
	Geo	13.3%	14	-5.2%	31.8%
	Non-Geo	10.7%	29	6.9%	14.6%
51-100 hp	All Industrial	14.5%	43	5.9%	23.1%
	Geo	1.2%	14	-0.5%	2.9%
	Non-Geo	20.7%	29	13.4%	28.0%
101-200 hp	All Industrial	0.0%	43	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	0.0%	29	0.0%	0.0%
201-500 hp	All Industrial	8.0%	43	-1.0%	16.9%
	Geo	25.2%	14	15.6%	34.8%
	Non-Geo	0.0%	29	0.0%	0.0%
501-1000 hp	All Industrial	6.8%	43	-0.8%	14.4%
	Geo	21.5%	14	13.3%	29.7%
	Non-Geo	0.0%	29	0.0%	0.0%
Greater than 1000 hp	All Industrial	9.6%	43	-1.2%	20.3%
	Geo	30.3%	14	18.7%	41.8%
	Non-Geo	0.0%	29	0.0%	0.0%



**Table C-12
Percent of Size Category Variable Load HP with VFDs**

Size Category	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1-5 hp	All Industrial	9.3%	40	-0.9%	19.4%
	Geo	3.5%	13	-2.1%	9.1%
	Non-Geo	28.3%	27	11.1%	45.5%
6-20 hp	All Industrial	31.9%	37	-2.2%	66.0%
	Geo	0.9%	13	-0.5%	2.3%
	Non-Geo	112.5%	24	86.7%	138.4%
21-50 hp	All Industrial	67.2%	30	36.2%	98.2%
	Geo	100.6%	10	37.3%	163.9%
	Non-Geo	56.5%	20	22.4%	90.6%
51-100 hp	All Industrial	56.5%	18	32.9%	80.1%
	Geo	7.1%	10	0.1%	14.2%
	Non-Geo	68.8%	8	44.0%	93.7%
101-200 hp	All Industrial	0.0%	16	0.0%	0.0%
	Geo	0.0%	8	0.0%	0.0%
	Non-Geo	0.0%	8	0.0%	0.0%
201-500 hp	All Industrial	64.0%	4	-52.4%	180.3%
	Geo	200.0%	3	200.0%	200.0%
	Non-Geo	0.0%	1	.	.
501-1000 hp	All Industrial	100.0%	1	.	.
	Geo	100.0%	1	.	.
	Non-Geo	0.0%	0	0.0%	0.0%
Greater than 1000 hp	All Industrial	100.0%	1	.	.
	Geo	100.0%	1	.	.
	Non-Geo	0.0%	0	0.0%	0.0%



**Table C-13
Average Number of Motors per Facility (Premise)**

Size Category	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
ALL	All Industrial	42.27	43	25.22	59.32
	Geo	93.43	14	76.30	110.56
	Non-Geo	29.89	29	18.77	41.00
1-5 hp	All Industrial	26.54	43	15.11	37.98
	Geo	63.77	14	49.87	77.66
	Non-Geo	17.53	29	11.77	23.29
6-20 hp	All Industrial	9.95	43	5.15	14.75
	Geo	26.13	14	21.50	30.76
	Non-Geo	6.03	29	3.07	9.00
21-50 hp	All Industrial	2.10	43	1.20	3.00
	Geo	1.27	14	(0.13)	2.67
	Non-Geo	2.30	29	1.23	3.36
51-100 hp	All Industrial	0.71	43	0.32	1.11
	Geo	1.83	14	1.36	2.29
	Non-Geo	0.45	29	0.13	0.76
101-200 hp	All Industrial	0.21	43	0.09	0.33
	Geo	0.23	14	(0.03)	0.50
	Non-Geo	0.21	29	0.07	0.35
201-500 hp	All Industrial	0.03	43	0.01	0.06
	Geo	0.09	14	(0.04)	0.21
	Non-Geo	0.02	29	(0.00)	0.05
500-1000 hp	All Industrial	0.00	43	(0.00)	0.01
	Geo	0.03	14	(0.02)	0.07
	Non-Geo	-	29	-	-
Greater than 1000 hp	All Industrial	0.00	43	(0.00)	0.01
	Geo	0.02	14	(0.01)	0.05
	Non-Geo	-	29	-	-



**Table C-14
Average Total Horsepower of Motors per Facility (Premise)**

Size Category	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
ALL	All Industrial	421	43	269	572
	Geo	839	14	661	1,017
	Non-Geo	320	29	186	453
1-5 hp	All Industrial	82	43	47	117
	Geo	185	14	145	225
	Non-Geo	57	29	35	80
6-20 hp	All Industrial	140	43	74	206
	Geo	343	14	283	404
	Non-Geo	91	29	44	138
21-50 hp	All Industrial	80	43	46	113
	Geo	46	14	(5)	98
	Non-Geo	88	29	47	128
51-100 hp	All Industrial	61	43	28	94
	Geo	143	14	107	180
	Non-Geo	41	29	12	69
101-200 hp	All Industrial	35	43	15	56
	Geo	39	14	(5)	83
	Non-Geo	34	29	11	58
201-500 hp	All Industrial	13	43	2	24
	Geo	34	14	(14)	81
	Non-Geo	8	29	(1)	18
500-1000 hp	All Industrial	4	43	(2)	9
	Geo	20	14	(14)	55
	Non-Geo	-	29	-	-
Greater than 1000 hp	All Industrial	6	43	(2)	13
	Geo	29	14	(20)	77
	Non-Geo	-	29	-	-



**Table C-15
Average Total Horsepower of NEMA Premium Motors per Facility (Premise)**

Size Category	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
ALL	All Industrial	29	43	6	53
	Geo	15	14	(3)	34
	Non-Geo	33	29	5	61
1-5 hp	All Industrial	2	43	1	3
	Geo	2	14	(1)	5
	Non-Geo	2	29	0	3
6-20 hp	All Industrial	7	43	2	12
	Geo	3	14	(1)	6
	Non-Geo	8	29	2	14
21-50 hp	All Industrial	18	43	(1)	36
	Geo	2	14	(0)	5
	Non-Geo	22	29	(1)	44
51-100 hp	All Industrial	2	43	0	3
	Geo	6	14	(3)	15
	Non-Geo	0	29	(0)	1
101-200 hp	All Industrial	1	43	(0)	3
	Geo	2	14	(1)	6
	Non-Geo	1	29	(1)	3
201-500 hp	All Industrial	-	43	-	-
	Geo	-	14	-	-
	Non-Geo	-	29	-	-
500-1000 hp	All Industrial	-	43	-	-
	Geo	-	14	-	-
	Non-Geo	-	29	-	-
Greater than 1000 hp	All Industrial	-	43	-	-
	Geo	-	14	-	-
	Non-Geo	-	29	-	-



**Table C-16
Average Total Horsepower of Motors with Variable Loads per Facility (Premise)**

Size Category	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
ALL	All Industrial	171	43	66	275
	Geo	554	14	412	695
	Non-Geo	78	29	30	126
1-5 hp	All Industrial	39	43	5	74
	Geo	155	14	88	223
	Non-Geo	11	29	5	18
6-20 hp	All Industrial	79	43	16	142
	Geo	292	14	183	401
	Non-Geo	27	29	8	46
21-50 hp	All Industrial	10	43	5	16
	Geo	12	14	(2)	27
	Non-Geo	10	29	4	16
51-100 hp	All Industrial	15	43	3	26
	Geo	15	14	0	30
	Non-Geo	15	29	1	29
101-200 hp	All Industrial	11	43	2	19
	Geo	18	14	(6)	42
	Non-Geo	9	29	0	18
201-500 hp	All Industrial	7	43	(1)	15
	Geo	12	14	(8)	32
	Non-Geo	6	29	(3)	15
500-1000 hp	All Industrial	4	43	(2)	9
	Geo	20	14	(14)	55
	Non-Geo	-	29	-	-
Greater than 1000 hp	All Industrial	6	43	(2)	13
	Geo	29	14	(20)	77
	Non-Geo	-	29	-	-



**Table C-17
Average Total Horsepower of Motors with VFDs per Facility (Premise)**

Size Category	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
ALL	All Industrial	58	43	17	99
	Geo	94	14	(43)	232
	Non-Geo	49	29	7	91
1-5 hp	All Industrial	4	43	1	6
	Geo	5	14	(2)	12
	Non-Geo	3	29	1	6
6-20 hp	All Industrial	25	43	4	46
	Geo	3	14	(1)	6
	Non-Geo	31	29	4	57
21-50 hp	All Industrial	7	43	2	11
	Geo	13	14	(5)	30
	Non-Geo	5	29	1	10
51-100 hp	All Industrial	8	43	(0)	17
	Geo	1	14	(0)	3
	Non-Geo	10	29	(1)	21
101-200 hp	All Industrial	-	43	-	-
	Geo	-	14	-	-
	Non-Geo	-	29	-	-
201-500 hp	All Industrial	5	43	(2)	11
	Geo	24	14	(17)	64
	Non-Geo	-	29	-	-
500-1000 hp	All Industrial	4	43	(2)	9
	Geo	20	14	(14)	55
	Non-Geo	-	29	-	-
Greater than 1000 hp	All Industrial	6	43	(2)	13
	Geo	29	14	(20)	77
	Non-Geo	-	29	-	-



**Table C-18
Percent of Total Motor Horsepower by End-Use (Premise)**

End Use	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Pumps	All Industrial	15.2%	43	5.6%	24.7%
	Geo	7.6%	14	-0.6%	15.7%
	Non-Geo	20.0%	29	7.0%	33.0%
Fans and Blowers	All Industrial	13.0%	43	6.7%	19.2%
	Geo	6.5%	14	2.0%	11.0%
	Non-Geo	17.1%	29	8.8%	25.4%
Air compressors	All Industrial	8.0%	43	4.5%	11.5%
	Geo	14.4%	14	6.3%	22.4%
	Non-Geo	4.0%	29	1.8%	6.2%
Refrigerant Compressor	All Industrial	1.8%	43	0.4%	3.2%
	Geo	0.9%	14	-0.1%	1.9%
	Non-Geo	2.3%	29	0.2%	4.4%
Materials Processing	All Industrial	50.2%	43	35.3%	65.0%
	Geo	64.6%	14	41.1%	88.1%
	Non-Geo	41.0%	29	28.5%	53.4%
Materials Handling	All Industrial	8.8%	43	3.5%	14.2%
	Geo	2.0%	14	-0.4%	4.4%
	Non-Geo	13.2%	29	5.8%	20.5%
Other	All Industrial	3.1%	43	0.3%	5.9%
	Geo	4.0%	14	-2.5%	10.5%
	Non-Geo	2.5%	29	-0.3%	5.3%



**Table C-19
Percent of Motors Associated with Component Type (Premise)**

Component	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Compressor	All Industrial	15.1%	42	1.4%	28.8%
	Geo	7.3%	14	0.0%	18.3%
	Non-Geo	17.0%	28	0.3%	33.8%
Pump	All Industrial	6.6%	42	3.1%	10.0%
	Geo	2.9%	14	0.0%	6.0%
	Non-Geo	7.5%	28	3.2%	11.8%
Fan	All Industrial	6.2%	42	1.7%	10.7%
	Geo	3.4%	14	0.0%	8.4%
	Non-Geo	6.9%	28	1.5%	12.4%
Blower	All Industrial	13.9%	42	1.6%	26.1%
	Geo	1.7%	14	0.0%	4.0%
	Non-Geo	16.8%	28	1.9%	31.7%
Vacuum Pump	All Industrial	1.5%	42	0.2%	2.8%
	Geo	1.1%	14	0.0%	2.9%
	Non-Geo	1.6%	28	0.0%	3.2%
Refrigerant Compressor	All Industrial	4.8%	42	0.0%	10.6%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	6.0%	28	0.0%	13.1%
Other Material Processing	All Industrial	45.4%	42	26.9%	63.9%
	Geo	82.6%	14	62.6%	100.0%
	Non-Geo	36.3%	28	17.2%	55.5%
Other Material Handling	All Industrial	5.7%	42	2.7%	8.6%
	Geo	1.1%	14	0.0%	2.5%
	Non-Geo	6.8%	28	3.3%	10.2%
Other	All Industrial	0.8%	42	0.1%	1.6%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	1.0%	28	0.1%	2.0%



**Table C-20
Percent of Motors with Load Modulation Type (Premise)**

Variable	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Throttle Valve	All Industrial	4.1%	38	0.7%	7.5%
	Geo	2.1%	13	0.0%	4.7%
	Non-Geo	4.9%	25	0.1%	9.7%
Vane/Damper	All Industrial	2.8%	38	0.0%	5.7%
	Geo	0.1%	13	0.0%	0.4%
	Non-Geo	3.9%	25	0.0%	8.2%
VFD	All Industrial	6.2%	38	2.6%	9.9%
	Geo	3.4%	13	0.0%	8.9%
	Non-Geo	7.4%	25	2.9%	11.9%
Staging	All Industrial	19.4%	38	0.0%	39.3%
	Geo	0.1%	13	0.0%	0.4%
	Non-Geo	27.3%	25	1.0%	53.6%
Multi-speed Motor	All Industrial	10.0%	38	3.4%	16.5%
	Geo	18.6%	13	11.3%	26.0%
	Non-Geo	6.4%	25	0.7%	12.1%
Eddy Current Clutch	All Industrial	0.1%	38	0.0%	0.3%
	Geo	0.0%	13	0.0%	0.0%
	Non-Geo	0.2%	25	0.0%	0.5%
Belt	All Industrial	18.1%	38	0.0%	37.4%
	Geo	0.9%	13	0.0%	2.4%
	Non-Geo	25.2%	25	0.5%	49.9%
Other Mechanical Drive	All Industrial	31.7%	38	16.3%	47.2%
	Geo	59.7%	13	41.8%	77.7%
	Non-Geo	20.1%	25	10.4%	29.9%
Other	All Industrial	7.5%	38	1.9%	13.2%
	Geo	14.9%	13	0.0%	34.5%
	Non-Geo	4.5%	25	0.5%	8.5%

**Table C-21
Percent of Motors by Type (Premise)**

Variable	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
AC Polyphase	All Industrial	67.6%	34	46.4%	88.8%
	Geo	87.8%	10	78.8%	96.8%
	Non-Geo	66.4%	24	43.6%	89.1%
AC Single Phase	All Industrial	31.7%	34	10.5%	52.9%
	Geo	12.0%	10	3.2%	20.8%
	Non-Geo	32.8%	24	10.1%	55.6%
DC	All Industrial	0.6%	34	0.0%	1.3%
	Geo	0.2%	10	0.0%	0.6%
	Non-Geo	0.7%	24	0.0%	1.4%
Synchronous	All Industrial	0.1%	34	0.0%	0.3%
	Geo	#N/A	#N/A	#N/A	#N/A
	Non-Geo	0.1%	24	0.0%	0.3%
Other	All Industrial	#N/A	#N/A	#N/A	#N/A
	Geo	#N/A	#N/A	#N/A	#N/A
	Non-Geo	#N/A	#N/A	#N/A	#N/A



**Table C-22
Percent of Motors with Enclosure Type (Premise)**

Variable	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
ODP	All Industrial	1.8%	31	0.1%	3.6%
	Geo	13.6%	10	1.8%	25.5%
	Non-Geo	1.3%	21	0.0%	2.8%
TEFC	All Industrial	97.9%	31	95.9%	99.8%
	Geo	79.7%	10	67.6%	91.8%
	Non-Geo	98.7%	21	97.2%	100.0%
Other	All Industrial	0.3%	31	0.0%	0.7%
	Geo	6.7%	10	0.0%	17.1%
	Non-Geo	#N/A	#N/A	#N/A	#N/A

**Table C-23
Miscellaneous Motor Details (Premise)**

Detail	Area	Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Black Box (Motor Not Visible) (Percent of Motors)	All Industrial	26.8%	42	14.5%	39.1%
	Geo	68.4%	14	59.8%	77.1%
	Non-Geo	16.6%	28	6.9%	26.4%
Variable Load (Percent of Motors)	All Industrial	53.2%	42	36.7%	69.6%
	Geo	74.8%	14	50.6%	99.0%
	Non-Geo	47.9%	28	29.9%	65.8%
Operating Hours per week	All Industrial	52	42	40	64
	Geo	70	14	59	81
	Non-Geo	48	28	34	61
Voltage Rating	All Industrial	302	39	250	354
	Geo	267	13	184	351
	Non-Geo	311	26	250	372
Horsepower	All Industrial	22	42	16	28
	Geo	42	14	20	64
	Non-Geo	20	28	14	26
kW	All Industrial	3.76	9	1	6
	Geo	5.91	3	4	8
	Non-Geo	3.22	6	0	6
Motor Speed (rpm)	All Industrial	2,907	40	2,134	3,680
	Geo	5,053	13	4,038	6,068
	Non-Geo	2,288	27	1,960	2,616
Nominal Efficiency Rating	All Industrial	85%	36	81%	90%
	Geo	88%	11	83%	93%
	Non-Geo	85%	25	80%	90%
Approximate Age	All Industrial	10	38	8	13
	Geo	6	13	3	9
	Non-Geo	12	25	9	15

C.1.2. Motor Energy Efficiency Opportunities

**Table C-24
Motor EE Ops (Premise)**

Energy Efficiency Opportunity	Area	Percent of Motors	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Replace with NEMA Premium Motor	All Industrial	28%	42	13%	43%
	Geo	18%	14	-2%	38%
	Non-Geo	31%	28	12%	49%
Install VSD	All Industrial	20%	42	8%	32%
	Geo	5%	14	-2%	11%
	Non-Geo	24%	28	9%	38%
Replace Gen-set for DC drive with silicon controlled rectifier	All Industrial	14%	36	-2%	30%
	Geo	0%	11	0%	0%
	Non-Geo	18%	25	-2%	37%
Other	All Industrial	2%	41	0%	5%
	Geo	0%	13	0%	0%
	Non-Geo	3%	28	0%	6%

Replace with NEMA Premium Motor 28.1%
 Install VSD 19.9%
 Replace Gen-set for DC drive with silicon controlled rectifier 14.0%
 Other 2.3%
 - 0.0%
 - 0.0%
 - 0.0%



Appendix D: Compressed Air Systems

D.1. Facility kWh Weighted Results

D.1.1. Compressed Air Details

Table D-1
Percent of Facilities with Air Compressor End Uses (Facility kWh)

End Use	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Percent of Facilities with Compressed Air Systems	All Industrial	94.5%	44	88.6%	100.0%
	Geo	80.9%	14	58.1%	100.0%
	Non-Geo	98.6%	30	96.7%	100.0%
Air Tool Drive	All Industrial	25.4%	42	17.9%	33.0%
	Geo	29.7%	14	13.8%	45.7%
	Non-Geo	24.0%	28	15.4%	32.6%
Open Blowing	All Industrial	18.1%	42	11.9%	24.2%
	Geo	16.8%	14	8.9%	24.6%
	Non-Geo	18.5%	28	10.5%	26.5%
Aeration, Agitation, Oxygenation of Liquids	All Industrial	1.6%	42	-0.5%	3.7%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	2.1%	28	-0.7%	4.9%
Transport of liquids or light solids (padding)	All Industrial	0.0%	42	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	0.0%	28	0.0%	0.0%
Transport of Solids	All Industrial	0.1%	42	0.0%	0.2%
	Geo	0.3%	14	-0.1%	0.7%
	Non-Geo	0.0%	28	0.0%	0.0%
Vacuum Generation	All Industrial	2.1%	42	0.8%	3.4%
	Geo	0.8%	14	-0.2%	1.8%
	Non-Geo	2.5%	28	0.8%	4.3%
Diaphragm Pumps	All Industrial	0.0%	42	0.0%	0.0%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	0.0%	28	0.0%	0.0%
Pneumatic Controls	All Industrial	49.2%	42	38.4%	60.0%
	Geo	44.4%	14	24.3%	64.5%
	Non-Geo	50.8%	28	37.9%	63.6%
Other	All Industrial	3.6%	42	0.5%	6.6%
	Geo	8.0%	14	-2.9%	18.9%
	Non-Geo	2.1%	28	0.1%	4.2%



**Table D-2
Air Compressor Details (Facility kWh)**

Question	Area	Percent/ Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
"Air" as Commodity Type	All Industrial	100%	42	100%	100%
	Geo	100%	14	100%	100%
	Non-Geo	100%	28	100%	100%
Average Number of Air Compressors	All Industrial	2.5	41	2.2	2.7
	Geo	2.7	13	2.2	3.1
	Non-Geo	2.4	28	2.1	2.7
Percent with Compressed Air Storage	All Industrial	75%	38	60%	90%
	Geo	74%	13	53%	95%
	Non-Geo	75%	25	56%	94%
Average Operating Capacity of Storage Tanks	All Industrial	348	29	214	482
	Geo	270	10	127	412
	Non-Geo	372	19	199	545
Percent with Sequencing Controls for Multiple Compressors	All Industrial	8.3%	23	2.1%	14.4%
	Geo	11.4%	10	-1.0%	23.7%
	Non-Geo	7.2%	13	-0.3%	14.7%

**Table D-3
Air Dryer System Details (Facility kWh)**

Question	Area	Percent/ Mean	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Percent of Facilities with Air Dryers	All Industrial	79%	41	68%	89%
	Geo	100%	14	100%	100%
	Non-Geo	71%	27	57%	86%
Percent of Facilities with Refrigerant Dryers	All Industrial	62%	39	49%	75%
	Geo	85%	12	70%	101%
	Non-Geo	56%	27	40%	73%
Percent of Facilities with Dessicant Dryers	All Industrial	12%	39	0.1	0.2
	Geo	3%	13	(0.0)	0.1
	Non-Geo	15%	26	0.1	0.2
Percent of Facilities with Deliquescent Dryers	All Industrial	1%	37	0%	3%
	Geo	0%	12	0%	0%
	Non-Geo	2%	25	-1%	4%



**Table D-4
Percent of Facilities with Compressed Air Unit Type (Facility kWh)**

Type of Unit	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Single Acting Reciprocating	All Industrial	29%	42	18%	41%
	Geo	30%	14	8%	52%
	Non-Geo	29%	28	15%	43%
Double Acting Reciprocating	All Industrial	12%	42	6%	18%
	Geo	5%	14	0%	11%
	Non-Geo	14%	28	6%	22%
Lubricant Injected Rotary Screw	All Industrial	44%	42	30%	57%
	Geo	44%	14	21%	67%
	Non-Geo	44%	28	27%	60%
Lubricant-Free Rotary Screw	All Industrial	33%	42	18%	48%
	Geo	30%	14	9%	51%
	Non-Geo	34%	28	15%	53%
Centrifugal	All Industrial	3%	42	0%	6%
	Geo	8%	14	-3%	19%
	Non-Geo	2%	28	-1%	4%
Other (Scroll)	All Industrial	3%	42	0%	6%
	Geo	2%	14	-1%	4%
	Non-Geo	3%	28	-1%	8%

**Table D-5
Percent of Facilities with Compressed Air Fuel Types (Facility kWh)**

Fuel Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Electric	All Industrial	99%	42	99%	100%
	Geo	100%	14	100%	100%
	Non-Geo	99%	28	98%	100%
Steam	All Industrial	0.6%	42	-0.2%	1.4%
	Geo	0.0%	14	0.0%	0.0%
	Non-Geo	0.8%	28	-0.3%	1.8%
Other (Diesel)	All Industrial	3%	42	0%	6%
	Geo	8%	14	-3%	19%
	Non-Geo	1%	28	0%	3%



**Table D-6
Percent of Facilities with Compressed Air Control Type (Facility kWh)**

Control Type	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Start-Stop	All Industrial	43%	37	29%	57%
	Geo	19%	13	-1%	38%
	Non-Geo	52%	24	32%	71%
Load/Unload	All Industrial	34%	37	21%	47%
	Geo	62%	13	39%	85%
	Non-Geo	23%	24	9%	37%
Modulating	All Industrial	35%	37	19%	51%
	Geo	33%	13	11%	55%
	Non-Geo	36%	24	15%	57%
Variable Displacement	All Industrial	2%	37	-1%	5%
	Geo	8%	13	-3%	20%
	Non-Geo	0%	24	0%	0%
Variable Speed Drive	All Industrial	3%	37	0%	5%
	Geo	9%	13	1%	18%
	Non-Geo	0%	24	0%	0%
Other	All Industrial	6%	37	-2%	13%
	Geo	21%	13	-4%	46%
	Non-Geo	0%	24	0%	0%

**Table D-7
Compressed Air EE Opportunities (Facility kWh)**

Opportunity	Area	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Reduce Leaks	All Industrial	32%	42	20%	43%
	Geo	43%	14	21%	65%
	Non-Geo	28%	28	14%	41%
Increase Air Storage	All Industrial	14%	42	6%	21%
	Geo	3%	14	-1%	8%
	Non-Geo	17%	28	7%	27%
Reduce Operating Pressures	All Industrial	12%	42	5%	19%
	Geo	16%	14	2%	30%
	Non-Geo	11%	28	2%	19%
Install Part Load Controllers	All Industrial	12%	42	4%	21%
	Geo	0%	14	0%	0%
	Non-Geo	16%	28	5%	27%
Install Unloading Kits	All Industrial	3%	42	0%	6%
	Geo	0%	14	0%	0%
	Non-Geo	4%	28	-1%	9%
Install Rotary Screw Air Compressors	All Industrial	11%	42	3%	18%
	Geo	0%	14	0%	0%
	Non-Geo	14%	28	4%	24%
Install Engineered Nozzles	All Industrial	26%	42	15%	38%
	Geo	25%	14	7%	44%
	Non-Geo	27%	28	12%	41%
Other	All Industrial	3%	42	0%	7%
	Geo	3%	14	-1%	8%
	Non-Geo	3%	28	-1%	8%



D.2. Premise Weighted Results

D.2.1. Compressed Air Details

Table D-8
Percent of Facilities with Air Compressor End Uses (Premise)

Table D-9
Horsepower Devoted to Compressed Air per Facility (Premise)

Appendix E: Refrigeration Results

Table E-1
Commercial Refrigerator Details

Detail	Site #1		
	Unit 1	Unit 2	Unit 3
Equipment Type	Glass Door Beverage Case	Glass Door Beverage Case	Glass Door Beverage Case
Length (feet)	5	10	8
Number of Doors	2	4	2
Number of Units	1	1	1
Age (Years)	18	18	18
EE Actions in Place			
Smart Anti-Sweat Heater Controls	No	No	No
Super High Insulation Freezer Wire	No	No	No
Economizer coolers	No	No	No
ECM Motors for Fans	No	No	No
EE Opportunities			
Smart Anti-Sweat Heater Controls	Yes	Yes	Yes
Super High Insulation Freezer Wire	Yes	Yes	Yes
Economizer coolers	Yes	Yes	Yes
ECM Motors for Fans	Yes	Yes	Yes

Table E-2
Non-Commercial Refrigerator Details

Site	Unit	Type	Quantity	Quantity Energy Star
Site #1	Unit 1	Single Door	2	0
	Unit 2	Under Counter	2	0
Site #2	Unit 1	Two Door	1	0
	Unit 2	Two Door	1	0
Site #3	Unit 1	Single Door	2	Unknown
	Unit 2	Under Counter	1	0
	Unit 3	Chest Freezer	1	Unknown
Site #4	Unit 1	Under Counter	1	0
Site #5	Unit 1	Single Door	2	1
Site #6	Unit 1	Two Door	1	0
Site #7	Unit 1	Single Door	1	0



Appendix F: Cooling Results

F.1.Premise Weighted Results

F.1.1. Overall Cooling

Table F-1
Percent of Facilities with Space Cooling of Type (Premise)

Cooling Type	Geo-Target	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
None	Overall	38%	44	18%	59%
	Geo-Target	3%	14	0%	7%
	Non-Geo-Target	47%	30	23%	70%
Packaged HVAC	Overall	26%	44	9%	43%
	Geo-Target	22%	14	-1%	44%
	Non-Geo-Target	27%	30	7%	48%
Split System HVAC	Overall	11%	44	5%	17%
	Geo-Target	7%	14	-3%	17%
	Non-Geo-Target	12%	30	4%	19%
Room A/C	Overall	29%	44	8%	49%
	Geo-Target	69%	14	38%	99%
	Non-Geo-Target	19%	30	-1%	39%
Other Central Cooling Plant	Overall	3%	44	0%	5%
	Geo-Target	7%	14	-3%	17%
	Non-Geo-Target	2%	30	-1%	4%
Heat Pump	Overall	17%	44	0%	34%
	Geo-Target	7%	14	-3%	17%
	Non-Geo-Target	19%	30	-1%	39%
Miscellaneous Cooling	Overall	16%	44	0%	31%
	Geo-Target	81%	14	61%	101%
	Non-Geo-Target	0%	30	0%	0%



**Table F-2
Percent of Units with Space Cooling of Type (Premise)**

Cooling Type	Geo-Target	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Packaged HVAC	Overall	24%	25	13%	36%
	Geo-Target	16%	9	1%	32%
	Non-Geo-Target	31%	16	20%	42%
Split System HVAC	Overall	20%	25	9%	32%
	Geo-Target	4%	9	-1%	10%
	Non-Geo-Target	34%	16	16%	51%
Room A/C	Overall	24%	25	10%	38%
	Geo-Target	31%	9	13%	48%
	Non-Geo-Target	18%	16	1%	36%
Other Central Cooling Plant	Overall	1%	25	0%	3%
	Geo-Target	1%	9	0%	3%
	Non-Geo-Target	1%	16	0%	3%
Heat Pump	Overall	9%	25	0%	18%
	Geo-Target	1%	9	-1%	4%
	Non-Geo-Target	16%	16	2%	29%
Miscellaneous Cooling	Overall	21%	25	8%	34%
	Geo-Target	46%	9	38%	53%
	Non-Geo-Target	0%	16	0%	0%



**Table F-3
Overall Space Cooling Details (Premise)**

Detail	Geo-Target	Percent or Quantity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Units Per Facility	Overall	3.1	25	2.2	4.0
	Geo-Target	4.7	9	3.5	5.8
	Non-Geo-Target	2.5	16	1.6	3.3
Average Age per Unit	Overall	11.8	15	10.2	13.4
	Geo-Target	12.7	5	10.1	15.3
	Non-Geo-Target	11.3	10	9.3	13.3
Percent of Units Missing Age	Overall	0.54	25	0.35	0.74
	Geo-Target	0.66	9	0.35	0.98
	Non-Geo-Target	0.45	16	0.30	0.59
Average Efficiency of Units (EER)	Overall	11.15	5	10.43	11.86
	Geo-Target	.	0	.	.
	Non-Geo-Target	11.15	5	10.43	11.86
Percent of Units Missing Efficiency	Overall	97%	25	95%	99%
	Geo-Target	100%	9	100%	100%
	Non-Geo-Target	95%	16	91%	98%
Average Unit Size (tons)	Overall	3.2	19	1.6	4.9
	Geo-Target	1.4	5	0.6	2.2
	Non-Geo-Target	4.1	14	2.0	6.1
Percent of Units Missing Size	Overall	53%	25	40%	66%
	Geo-Target	67%	9	51%	82%
	Non-Geo-Target	42%	16	18%	65%
Average Amount of Space Cooling (tons) per Facility	Overall	6.6	19	2.1	11.1
	Geo-Target	2.6	5	1.4	3.9
	Non-Geo-Target	8.8	14	1.6	16.1



F.1.2. Central Cooling Plant

Table F-4
Percent of Facilities with Central Cooling Plants by Type (Premise)

Type of Central Cooling Plant	Geo-Target	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
No Central Cooling Plant	Overall	74%	44	57%	91%
	Geo-Target	84%	14	66%	102%
	Non-Geo-Target	72%	30	51%	92%
Central Cooling Plant	Overall	26%	44	9%	43%
	Geo-Target	16%	14	-2%	34%
	Non-Geo-Target	28%	30	8%	49%
Packaged HVAC	Overall	18%	44	1%	35%
	Geo-Target	1%	14	0%	3%
	Non-Geo-Target	22%	30	2%	42%
Split System HVAC	Overall	0%	44	0%	0%
	Geo-Target	0%	14	0%	0%
	Non-Geo-Target	0%	30	0%	0%
Misc Central Cooling Plant	Overall	6%	44	2%	9%
	Geo-Target	8%	14	-3%	20%
	Non-Geo-Target	5%	30	1%	9%
Heat Pump	Overall	3%	44	0%	5%
	Geo-Target	7%	14	-3%	17%
	Non-Geo-Target	2%	30	-1%	4%

Table F-5
Percent of Central Cooling Plant Premises by Type (Premise)

Cooling Type	Geo-Target	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Packaged HVAC	Overall	69%	18	44%	94%
	Geo-Target	8%	7	-1%	17%
	Non-Geo-Target	77%	11	56%	99%
Split System HVAC	Overall	0%	18	0%	0%
	Geo-Target	0%	7	0%	0%
	Non-Geo-Target	0%	11	0%	0%
Misc Central Cooling Plant	Overall	21%	18	3%	39%
	Geo-Target	52%	7	14%	90%
	Non-Geo-Target	17%	11	0%	34%
Heat Pump	Overall	10%	18	-1%	21%
	Geo-Target	40%	7	2%	79%
	Non-Geo-Target	6%	11	-3%	14%



**Table F-6
Percent of Central Cooling Plant Premises by Fuel (Premise)**

Fuel Type	Geo-Target	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Electric	Overall	45%	18	11%	79%
	Geo-Target	96%	7	90%	102%
	Non-Geo-Target	38%	11	5%	71%
Natural Gas	Overall	55%	18	20%	89%
	Geo-Target	0%	7	0%	0%
	Non-Geo-Target	62%	11	29%	95%
Unknown	Overall	0%	18	0%	1%
	Geo-Target	4%	7	-2%	10%
	Non-Geo-Target	0%	11	0%	0%

**Table F-7
Percent of Central Cooling Plant Cooling Equipment Units by Fuel (Premise)**

Fuel Type	Geo-Target	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Electric	Overall	63%	18	31%	95%
	Geo-Target	97%	7	92%	101%
	Non-Geo-Target	59%	11	25%	94%
Natural Gas	Overall	37%	18	4%	69%
	Geo-Target	0%	7	0%	0%
	Non-Geo-Target	41%	11	6%	75%
Unknown	Overall	0%	18	0%	1%
	Geo-Target	3%	7	-1%	8%
	Non-Geo-Target	0%	11	0%	0%



**Table F-8
Output (Tons) of Central Cooling Plant Equipment (Premise)**

Output Capacity	Geo-Target	Tons	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Tons Per Plant Devoted to Space Cooling	Overall	19.9	7	10.3	29.5
	Geo-Target	10.6	3	1.1	20.2
	Non-Geo-Target	23.1	4	11.7	34.5
Total Tons Cooling Per Plant	Overall	36.9	11	24.5	49.3
	Geo-Target	17.5	4	0.6	34.4
	Non-Geo-Target	42.5	7	29.2	55.8
Tons Per Unit Devoted to Space Cooling	Overall	9.5	7	7.6	11.3
	Geo-Target	8.6	3	3.1	14.0
	Non-Geo-Target	9.6	4	7.7	11.5
Tons Per Unit	Overall	19.4	11	11.5	27.3
	Geo-Target	13.5	4	3.9	23.1
	Non-Geo-Target	20.5	7	11.0	30.0
Percent of Central Cooling Plants with Known Tons Space Cooling	Overall	31%	18	9%	54%
	Geo-Target	48%	7	15%	82%
	Non-Geo-Target	30%	11	6%	53%
Percent of Central Cooling Plants with Known Tons Cooling	Overall	35%	18	12%	59%
	Geo-Target	55%	7	22%	88%
	Non-Geo-Target	33%	11	9%	58%

**Table F-9
EE Ops for Central Cooling Plant Fans and Blowers (Premise)**

Energy Efficiency Opportunity	Geo-Target	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Reduce Fan Size to Better Match Load	Overall	0%	18	0%	0%
	Geo-Target	0%	7	0%	0%
	Non-Geo-Target	0%	11	0%	0%
Replace Damper and Vane Controls with Electronic Speed Controls	Overall	10%	18	-1%	21%
	Geo-Target	0%	7	0%	0%
	Non-Geo-Target	11%	11	-2%	25%
Replace Fan with more Efficient Model	Overall	7%	18	-1%	15%
	Geo-Target	0%	7	0%	0%
	Non-Geo-Target	8%	11	-2%	17%
Other Fan Measure	Overall	0%	18	0%	0%
	Geo-Target	0%	7	0%	0%
	Non-Geo-Target	0%	11	0%	0%



**Table F-10
EE Ops for Packaged Central Cooling Plants (Premise)**

Energy Efficiency Opportunities	Geo-Target	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Install Economizer	Overall	1%	7	-1%	3%
	Geo-Target	100%	2	100%	100%
	Non-Geo-Target	0%	5	0%	0%
Install Demand Control Ventilation	Overall	10%	7	-4%	25%
	Geo-Target	50%	2	3%	97%
	Non-Geo-Target	10%	5	-4%	24%

**Table F-11
Average Operating Weeks of Central Cooling Plants (Premise)**

Output Capacity	Geo-Target	Tons	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Average Weeks in Operation for Cooling Plants used Seasonally	Overall	23.1	9	15.4	30.8
	Geo-Target	24.0	4	19.7	28.3
	Non-Geo-Target	23.0	5	14.6	31.5
Percent of Facilities for whom operating weeks are Unknown	Overall	5%	18	(0.0)	0.1
	Geo-Target	7%	7	(0.0)	0.1
	Non-Geo-Target	5%	11	(0.0)	0.1
Less than 13 weeks per year	Overall	-	18	-	-
	Geo-Target	-	7	-	-
	Non-Geo-Target	-	11	-	-
13 to 26	Overall	68%	18	0.5	0.9
	Geo-Target	42%	7	0.1	0.8
	Non-Geo-Target	70%	11	0.5	0.9
26 to 39	Overall	4%	18	-1%	9%
	Geo-Target	42%	7	8%	75%
	Non-Geo-Target	0%	11	0%	0%
39 to 52	Overall	0%	18	0%	1%
	Geo-Target	3%	7	-1%	8%
	Non-Geo-Target	0%	11	0%	0%
Not Seasonal	Overall	23%	18	4%	42%
	Geo-Target	7%	7	-3%	16%
	Non-Geo-Target	25%	11	3%	46%



**Table F-12
Average Operating Hours of Central Cooling Plants (Premise)**

Output Capacity	Geo-Target	Tons	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Average Weekly Hours of Operation	Overall	92.1	11	65.5	118.7
	Geo-Target	107.3	4	58.0	156.6
	Non-Geo-Target	90.7	7	62.4	119.0
Percent of Facilities for whom Operating Hours are Unknown	Overall	8%	18	0.0	0.1
	Geo-Target	13%	7	0.0	0.3
	Non-Geo-Target	7%	11	0.0	0.1
Less than 40 hours per week	Overall	-	18	-	-
	Geo-Target	-	7	-	-
	Non-Geo-Target	-	11	-	-
40 to 56	Overall	24%	18	0.0	0.4
	Geo-Target	42%	7	0.1	0.8
	Non-Geo-Target	22%	11	0.0	0.4
56 to 84	Overall	37%	18	4%	69%
	Geo-Target	0%	7	0%	0%
	Non-Geo-Target	41%	11	6%	75%
84 to 120	Overall	0%	18	0%	0%
	Geo-Target	0%	7	0%	0%
	Non-Geo-Target	0%	11	0%	0%
120 to 168	Overall	31%	18	9%	53%
	Geo-Target	45%	7	11%	79%
	Non-Geo-Target	30%	11	6%	53%



F.2.Packaged Cooling

F.2.1. Premise Weighted Results

F.2.1.1. Details

Table F-13
Unit Type by Geo-Target (premise)

Unit Type	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Packaged A/C	All-Industrial	8	67%	40%	95%
	Geo	4	65%	15%	115%
	Non-Geo	4	70%	23%	117%
Packaged Heat Pump	All-Industrial	0	0%	0%	0%
	Geo	0	0%	0%	0%
	Non-Geo	0	0%	0%	0%
Packaged A/C w/ Water Loop	All-Industrial	0	0%	0%	0%
	Geo	0	0%	0%	0%
	Non-Geo	0	0%	0%	0%
Packaged Heat Pump w/ Water Loop	All-Industrial	0	0%	0%	0%
	Geo	0	0%	0%	0%
	Non-Geo	0	0%	0%	0%
Packaged Split System	All-Industrial	8	16%	-6%	38%
	Geo	4	0%	0%	0%
	Non-Geo	4	30%	-17%	77%
Evaporative Cooler	All-Industrial	0	0%	0%	0%
	Geo	0	0%	0%	0%
	Non-Geo	0	0%	0%	0%
Other	All-Industrial	8	17%	-5%	38%
	Geo	4	35%	-15%	85%
	Non-Geo	4	0%	0%	0%
Don't Know	All-Industrial	0	0%	0%	0%
	Geo	0	0%	0%	0%
	Non-Geo	0	0%	0%	0%
Not Applicable	All-Industrial	0	0%	0%	0%
	Geo	0	0%	0%	0%
	Non-Geo	0	0%	0%	0%



**Table F-14
Number of Units of a Common Size and Type by Geo-Target (premise)**

Unit Type	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1	All-Industrial	8	68%	41%	95%
	Geo	4	32%	-18%	82%
	Non-Geo	4	100%	100%	100%
2 to 5	All-Industrial	8	31%	4%	58%
	Geo	4	65%	15%	115%
	Non-Geo	4	0%	0%	0%
Greater than 5	All-Industrial	8	1%	-1%	4%
	Geo	4	3%	-3%	10%
	Non-Geo	4	0%	0%	0%
Don't Know	All-Industrial	0	0%	0%	0%
	Geo	0	0%	0%	0%
	Non-Geo	0	0%	0%	0%
Not Applicable	All-Industrial	0	0%	0%	0%
	Geo	0	0%	0%	0%
	Non-Geo	0	0%	0%	0%

**Table F-15
Rated Output by Geo-Target (premise)**

Primary Fuel	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
0 to 2	All-Industrial	8	21%	-2%	44%
	Geo	4	0%	0%	0%
	Non-Geo	4	40%	-8%	88%
2 to 4	All-Industrial	8	15%	-6%	37%
	Geo	4	32%	-18%	82%
	Non-Geo	4	0%	0%	0%
4 to 6	All-Industrial	8	32%	4%	59%
	Geo	4	0%	0%	0%
	Non-Geo	4	60%	12%	108%
Don't know	All-Industrial	8	32%	5%	59%
	Geo	4	68%	18%	118%
	Non-Geo	4	0%	0%	0%
Not Applicable	All-Industrial	0	0%	0%	0%
	Geo	0	0%	0%	0%
	Non-Geo	0	0%	0%	0%



**Table F-16
Heating Fuel by Geo-Target (premise)**

Heating Fuel	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Less than 5	All-Industrial	8	49%	20%	78%
	Geo	4	3%	-3%	10%
	Non-Geo	4	90%	70%	110%
5 to 10	All-Industrial	8	31%	4%	58%
	Geo	4	65%	15%	115%
	Non-Geo	4	0%	0%	0%
10 to 20	All-Industrial	8	5%	-3%	13%
	Geo	4	0%	0%	0%
	Non-Geo	4	10%	-10%	30%
Greater than 20	All-Industrial	8	15%	-6%	37%
	Geo	4	32%	-18%	82%
	Non-Geo	4	0%	0%	0%
Don't know	All-Industrial	0	0%	0%	0%
	Geo	0	0%	0%	0%
	Non-Geo	0	0%	0%	0%

**Table F-17
Equipment Share by Unit Type by Geo-Target (premise)**

Equipment Share by Unit Type	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1	All-Industrial	8	45%	13%	76%
	Geo	4	37%	-10%	84%
	Non-Geo	4	70%	23%	117%
5	All-Industrial	8	7%	-4%	18%
	Geo	4	0%	0%	0%
	Non-Geo	4	30%	-17%	77%
7	All-Industrial	8	48%	15%	81%
	Geo	4	63%	16%	110%
	Non-Geo	4	0%	0%	0%



**Table F-18
Average Values by Geo-Target (premise)**

Average Values	Area	# Cases	Weighted Average	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Number of units of this size and type	All-Industrial	8	2	1	3
	Geo	4	4	1	6
	Non-Geo	4	1	1	1
Performance Rating Value (EER)	All-Industrial	5	3	2	4
	Geo	1	3	.	.
	Non-Geo	4	3	1	5
Qty. of Fans	All-Industrial	8	8	4	13
	Geo	4	14	7	20
	Non-Geo	4	4	1	6



Appendix G: Heating Results

G.1. Premise Weighted Results

G.1.1. Central Heating Plant

**Table G-1
Percent of Facilities with Central Heating Plant of Type (Premise)**

Heating Type	Geo-Target	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Percent of Facilities with a Central Heating Plant	Overall	81%	44	64%	98%
	Geo-Target	92%	14	80%	103%
	Non-Geo-Target	78%	30	58%	98%
Hot Water Boiler	Overall	17%	33	4%	29%
	Geo-Target	2%	10	-1%	5%
	Non-Geo-Target	24%	23	4%	44%
Steam Boiler	Overall	5%	33	1%	9%
	Geo-Target	3%	10	-1%	7%
	Non-Geo-Target	6%	23	1%	11%
Furnace	Overall	27%	33	4%	50%
	Geo-Target	72%	10	41%	103%
	Non-Geo-Target	6%	23	0%	11%
Direct Fired Radiant	Overall	28%	33	3%	53%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	42%	23	14%	69%
Other Direct Heating	Overall	8%	33	-2%	17%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	11%	23	-3%	26%
Packaged HVAC	Overall	8%	33	-2%	18%
	Geo-Target	23%	10	-6%	52%
	Non-Geo-Target	1%	23	0%	2%
Unknown	Overall	7%	33	1%	13%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	10%	23	3%	17%



**Table G-2
Percent of Units with Central Heating Plant of Type (Premise)**

Heating Type	Geo-Target	Percent	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Electric	Overall	0%	33	0%	0%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	0%	23	0%	0%
Natural Gas	Overall	46%	33	17%	75%
	Geo-Target	27%	10	-4%	57%
	Non-Geo-Target	56%	23	23%	88%
Propane	Overall	26%	33	9%	44%
	Geo-Target	13%	10	-3%	29%
	Non-Geo-Target	33%	23	7%	59%
Waste Heat	Overall	0%	33	0%	0%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	0%	23	0%	0%
Purchased Steam	Overall	0%	33	0%	0%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	0%	23	0%	0%
Fuel Oil	Overall	26%	33	3%	49%
	Geo-Target	59%	10	22%	97%
	Non-Geo-Target	10%	23	2%	19%
Wood	Overall	1%	33	0%	2%
	Geo-Target	1%	10	0%	1%
	Non-Geo-Target	1%	23	0%	2%
Unknown	Overall	0%	33	0%	1%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	0%	23	0%	1%

**Table G-3
Central Heating Plant Output (Premise)**

Detail	Geo-Target	Percent or Quantity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Output Per Unit (Mbtu/hr)	Overall	854	23	333	1,374
	Geo-Target	299	7	100	498
	Non-Geo-Target	1,537	16	727	2,347
Output Per Facility (Mbtu/hr)	Overall	1,754	23	825	2,683
	Geo-Target	953	7	293	1,613
	Non-Geo-Target	2,195	16	836	3,555
Percent of Units with Unknown Output Capacity	Overall	56%	33	29%	82%
	Geo-Target	23%	10	-6%	52%
	Non-Geo-Target	72%	23	49%	94%
Percent of Output Capacity used for Space Heat	Overall	52%	23	30%	75%
	Geo-Target	65%	7	37%	94%
	Non-Geo-Target	49%	16	23%	75%
Percent of Output Capacity used for Process Heat	Overall	46%	23	23%	69%
	Geo-Target	30%	7	1%	59%
	Non-Geo-Target	50%	16	24%	77%
Percent of Output Capacity used for Other Heat	Overall	1%	23	0%	3%
	Geo-Target	4%	7	0%	9%
	Non-Geo-Target	1%	16	0%	2%



**Table G-4
Central Heating Plant Output Categories (Premise)**

Detail	Geo-Target	Percent or Quantity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Less than 100 Mbtu	Overall	3%	33	0%	6%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	4%	23	0%	8%
100-500	Overall	22%	33	3%	41%
	Geo-Target	82%	10	60%	103%
	Non-Geo-Target	5%	23	1%	10%
500-1,000	Overall	21%	33	1%	41%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	26%	23	2%	51%
1000-5,000	Overall	8%	33	3%	14%
	Geo-Target	9%	10	-3%	22%
	Non-Geo-Target	8%	23	2%	15%
5,000-10,000	Overall	1%	33	0%	1%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	1%	23	0%	2%
Greater than 10,000 Mbtu	Overall	1%	33	0%	2%
	Geo-Target	1%	10	0%	2%
	Non-Geo-Target	1%	23	0%	3%
Unknown Capacity	Overall	44%	33	21%	67%
	Geo-Target	9%	10	-4%	21%
	Non-Geo-Target	54%	23	28%	79%



**Table G-5
Central Heating Plant Details (Premise)**

Detail	Geo-Target	Percent or Quantity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Average Age per Unit	Overall	14.7	30	11.8	17.6
	Geo-Target	19.3	9	17.9	20.7
	Non-Geo-Target	12.4	21	10.2	14.7
Percent of Units Missing Age	Overall	4%	33	0%	7%
	Geo-Target	4%	10	-2%	9%
	Non-Geo-Target	4%	23	0%	8%
Average Annual Operating Hours	Overall	1,917	24	1,404	2,431
	Geo-Target	1,428	7	938	1,917
	Non-Geo-Target	2,114	17	1,400	2,828
Percent Missing Annual Operating Hours	Overall	14%	33	2%	25%
	Geo-Target	23%	10	-6%	53%
	Non-Geo-Target	9%	23	1%	16%
Average Percent of Capacity while Operating	Overall	60%	25	33%	86%
	Geo-Target	99%	8	98%	100%
	Non-Geo-Target	44%	17	23%	65%
Missing Percent Operating Capacity	Overall	21%	33	5%	37%
	Geo-Target	32%	10	-1%	65%
	Non-Geo-Target	16%	23	0%	32%
Average Steam Pressure (psi)	Overall	25.1	8	7.2	43.0
	Geo-Target	18.1	3	(0.3)	36.4
	Non-Geo-Target	27.7	5	4.5	51.0
Percent of Units with Unknown Steam Pressure	Overall	95%	33	91%	99%
	Geo-Target	97%	10	94%	101%
	Non-Geo-Target	94%	23	88%	100%
Average Steam Temperature (F°)	Overall	176	7	136	215
	Geo-Target	138	3	87	188
	Non-Geo-Target	206	4	196	217
Percent of Units with Unknown Steam Temperature	Overall	97%	33	95%	99%
	Geo-Target	97%	10	94%	101%
	Non-Geo-Target	97%	23	94%	100%



**Table G-6
Central Heating Plant Age Categories (Premise)**

Detail	Geo-Target	Percent or Quantity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Less than 5 years Old	Overall	1%	33	0%	3%
	Geo-Target	2%	10	0%	5%
	Non-Geo-Target	1%	23	0%	2%
5-10	Overall	9%	33	0%	19%
	Geo-Target	0%	10	0%	1%
	Non-Geo-Target	14%	23	-1%	29%
10-20	Overall	45%	33	17%	74%
	Geo-Target	11%	10	-3%	25%
	Non-Geo-Target	62%	23	33%	91%
20-30	Overall	38%	33	13%	63%
	Geo-Target	82%	10	64%	100%
	Non-Geo-Target	16%	23	0%	33%
30-40	Overall	1%	33	0%	2%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	2%	23	0%	3%
40-50	Overall	0%	33	0%	0%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	0%	23	0%	0%
50-60	Overall	1%	33	0%	2%
	Geo-Target	0%	10	0%	0%
	Non-Geo-Target	1%	23	0%	3%
Percent of Units with Unknown Age	Overall	4%	33	1%	8%
	Geo-Target	4%	10	-2%	10%
	Non-Geo-Target	4%	23	0%	8%



**Table G-7
Central Heating Plant EE Ops**

EE Opportunity	Geo-Target	Percent or Quantity	# of Cases	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Install Economizer	Overall	20%	33	0%	39%
	Geo-Target	82%	10	62%	103%
	Non-Geo-Target	2%	23	-1%	5%
Install Demand Control Ventilation	Overall	21%	33	1%	41%
	Geo-Target	8%	10	-4%	19%
	Non-Geo-Target	24%	23	0%	49%
Replace Furnace/Boiler	Overall	42%	33	19%	65%
	Geo-Target	82%	10	60%	103%
	Non-Geo-Target	31%	23	7%	56%
Install Set-back Controls	Overall	46%	33	23%	69%
	Geo-Target	82%	10	60%	103%
	Non-Geo-Target	36%	23	11%	61%
Replace Steam Traps	Overall	3%	33	0%	7%
	Geo-Target	8%	10	-4%	19%
	Non-Geo-Target	2%	23	-1%	5%
Regularly Tune Boilers	Overall	28%	33	8%	49%
	Geo-Target	9%	10	-4%	21%
	Non-Geo-Target	34%	23	9%	59%
Other	Overall	2%	33	-1%	4%
	Geo-Target	7%	10	-4%	18%
	Non-Geo-Target	0%	23	0%	0%



G.2. Miscellaneous Heating

G.2.1. Premise Weighted Results

G.2.1.1. Details

Table G-8
Number of Units of the Same Size and Type by Geo-Target (Premise)

Unit Type	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
1	All-Industrial	5	51%	-4%	107%
	Geo	3	9%	-17%	34%
	Non-Geo	2	92%	44%	139%
2	All-Industrial	5	56%	1%	112%
	Geo	3	10%	-17%	36%
	Non-Geo	2	100%	100%	100%
3	All-Industrial	5	44%	-12%	99%
	Geo	3	90%	64%	117%
	Non-Geo	2	0%	0%	0%
4	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
5	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
6	All-Industrial	5	47%	-9%	103%
	Geo	3	0%	0%	0%
	Non-Geo	2	92%	44%	139%
Don't know	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
Not Applicable	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%



Table G-9
Percent of Output Used for Space Heat by Geo-Target (Premise)

Percent of Output Used for Space Heat	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Less than 25%	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
25 to 50%	All-Industrial	5	96%	87%	104%
	Geo	3	91%	66%	117%
	Non-Geo	2	100%	100%	100%
50 to 75%	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
75 to 100%	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
Unknown	All-Industrial	5	4%	-4%	13%
	Geo	3	9%	-17%	34%
	Non-Geo	2	0%	0%	0%

Table G-10
Percent of Output Used for Process Heat by Geo-Target (Premise)

Percent of Output Used for Process Heat	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Less than 25%	All-Industrial	5	44%	-12%	99%
	Geo	3	90%	64%	117%
	Non-Geo	2	0%	0%	0%
25 to 50%	All-Industrial	5	56%	1%	112%
	Geo	3	10%	-17%	36%
	Non-Geo	2	100%	100%	100%
50 to 75%	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
75 to 100%	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%



**Table G-11
Percent of Output for Other Uses by Geo-Target (Premise)**

Percent of Output for Other Uses	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Less than 25%	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
25 to 50%	All-Industrial	5	52%	-3%	107%
	Geo	3	10%	-17%	36%
	Non-Geo	2	92%	44%	139%
50 to 75%	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
75 to 100%	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
Unknown	All-Industrial	5	48%	-7%	103%
	Geo	3	90%	64%	117%
	Non-Geo	2	8%	-39%	56%

**Table G-12
Average Values by Geo-Target (Premise)**

Average Values	Area	# Cases	Weighted Average	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Number of units of this size and type	All-Industrial	5	3	3	3
	Geo	3	3	2	3
	Non-Geo	2	3	2	3
Qty. of Fans	All-Industrial	4	1	1	1
	Geo	2	1	0	1
	Non-Geo	2	1	1	1



**Table G-13
Heating Equipment Type by Geo-Target (Premise)**

Primary Fuel	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Electric baseboard heat	All-Industrial	5	44%	-12%	99%
	Geo	3	90%	64%	117%
	Non-Geo	2	0%	0%	0%
Unit heaters	All-Industrial	5	9%	-5%	22%
	Geo	3	9%	-17%	34%
	Non-Geo	2	8%	-39%	56%
Cabinet unit heaters	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
Packaged Terminal Heat Pump (PTHP)	All-Industrial	5	4%	-4%	13%
	Geo	3	9%	-17%	34%
	Non-Geo	2	0%	0%	0%
Other	All-Industrial	5	48%	-8%	103%
	Geo	3	1%	-2%	3%
	Non-Geo	2	92%	44%	139%
Don't know	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
Not Applicable	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%

**Table G-14
Heating Fuel by Geo-Target (Premise)**

Heating Fuel	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Electricity	All-Industrial	5	44%	-11%	100%
	Geo	3	91%	66%	117%
	Non-Geo	2	0%	0%	0%
Natural Gas	All-Industrial	5	4%	-4%	13%
	Geo	3	9%	-17%	34%
	Non-Geo	2	0%	0%	0%
Other	All-Industrial	5	52%	-4%	107%
	Geo	3	0%	0%	0%
	Non-Geo	2	100%	100%	100%
Don't know	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
Not Applicable	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%



**Table G-15
Energy Star Equipment by Geo-Target (Premise)**

Energy Star Equipment	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Yes	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
No	All-Industrial	5	56%	1%	112%
	Geo	3	10%	-17%	36%
	Non-Geo	2	100%	100%	100%
Don't Know	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
Not Applicable	All-Industrial	5	48%	-7%	103%
	Geo	3	99%	97%	102%
	Non-Geo	2	0%	0%	0%

**Table G-16
Quantity of Fans by Geo-Target (Premise)**

Quantity of Fans	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Yes	All-Industrial	5	56%	0%	111%
	Geo	3	9%	-17%	34%
	Non-Geo	2	100%	100%	100%
No	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
Don't Know	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
Not Applicable	All-Industrial	5	44%	-12%	99%
	Geo	3	90%	64%	117%
	Non-Geo	2	0%	0%	0%



**Table G-17
Rated Output in Mbtuh by Geo-Target (Premise)**

Rated Output in Mbtuh	Area	# Cases	Weighted Percent	Lower 80% Confidence Limit	Upper 80% Confidence Limit
Less than 100	All-Industrial	5	4%	-4%	13%
	Geo	3	0%	0%	0%
	Non-Geo	2	8%	-39%	56%
100 to 500	All-Industrial	5	51%	-4%	107%
	Geo	3	9%	-17%	34%
	Non-Geo	2	92%	44%	139%
500 to 1,000	All-Industrial	5	44%	-11%	100%
	Geo	3	91%	66%	117%
	Non-Geo	2	0%	0%	0%
1,000 to 5,000	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
5,000 to 10,000	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%
Greater than 10,000	All-Industrial	5	0%	0%	0%
	Geo	3	0%	0%	0%
	Non-Geo	2	0%	0%	0%